

Code: XVR301-04G

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **XVR301-04G** 4 CHANNELS UNIVIEW

The XVR301-04G digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



Standard:	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs:	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Video outputs:	• 1 pcs HDMI • 1 pcs VGA
Audio inputs:	• 1 pcs CINCH, • 4 Channels - Coaxial audio - Audio support via coaxial cable
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 / H.264
Image records resolutions:	• HD-TVI / AHD : 5M-N - 1296 x 1944 , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • HD-CVI : 5M-N - 1296 x 1944 1 CH only , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • PAL : 960H - 960 x 576 , • IP : max. 4 Mpx - 2560 x 1440



DATA SHEET

Recording speed adjustment:	4 Mpx IP @ 1 ... 25 fps 5M-N @ 1 ... 12 fps 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 15 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Operation modes:	4 x HD-TVI / AHD / HD-CVI / CVBS / IP + 2 x IP
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 8 TB SATA
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, backward, fast, slow. All channels synchronous playback, Smart Search function
Network interface:	1 x RJ-45 - 10/100 Base-TX
Bitrate:	max. 24 Mbps
Network functions:	Live image view, Playback the records, Remote configuration, Web Server built-in, 128 on-line users
Network protocols:	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address:	DHCP or 192.168.1.30
Default admin user / password:	admin / 123456
Web browser access ports:	80, 554
PC client access ports:	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports:	80
RTSP URL:	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
Alarm inputs / outputs:	—
PTZ control:	PTZ Uniview cameras
Motion Detection:	✓
USB:	2 x USB 2.0
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A (power adapter included)
Color:	Black
Weight:	0.94 kg
Dimensions:	260 x 252 x 45 mm



DATA SHEET

Supported languages:	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian, Hungarian
Country of origin:	China
Manufacturer / Brand:	UNIVIEW
Guarantee:	3 years

