

Code: TMS-5/8S

## MULTISWITCH **TMS-5/8S** 5 INPUTS / 8 OUTPUTS TRIAX



Inputs:	<ul style="list-style-type: none"> <li>• 1 x 47 MHz ... 694 MHz - Active / 5 MHz ... 862 MHz - Passive,</li> <li>• 4 x 950 MHz ... 2200 MHz</li> </ul>
Outputs:	8 x 47 ... 2200 MHz
TV amplification (cable pre-correction):	0 dB
SAT amplification (cable pre-correction):	-2 ... 3 dB
Isolation:	<ul style="list-style-type: none"> <li>• Interpolarized H/V : 30 dB</li> <li>• Between inputs SAT/TV : 30 dB</li> <li>• Outputs : 30 dB - SAT</li> <li>• Outputs : 25 dB - TV</li> </ul>
Return loss:	TV input : > 10 dB SAT input : > 10 dB Outputs : > 10 dB
Maximal output level SAT:	100 dB $\mu$ V (-35dB IMD3)
Maximal output level TV:	90 dB $\mu$ V (-60dB IMD3)
Switching signals:	13 V / 18 V, 0 / 22 kHz, DiSEqC 1.0, DiSEqC 2.0
LNB power supply:	max. 1000 mA
Pre-amplifiers powering:	—
Power supply:	180 ... 264 V AC
Weight:	0.76 kg
Dimensions:	250 x 145 x 62 mm
Manufacturer / Brand:	TRIAx



# DATA SHEET

---

Guarantee:	6 years
------------	---------