

Code: BCS-B-NVR1601(2.0)

## NVR **BCS-B-NVR1601(2.0)** 16 CHANNELS BCS BASIC



|                                     |                                                                                                                                                                                         |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                                  |
| Supported resolutions:              | max. 8 Mpx 4K UHD - 3840 x 2160 px                                                                                                                                                      |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA                                                                                                                                                              |
| Audio support:                      | 16 Channels - Audio from cameras                                                                                                                                                        |
| Audio inputs:                       | —                                                                                                                                                                                       |
| Audio outputs:                      | 1 pcs Jack 3.5 mm socket                                                                                                                                                                |
| Image compression method:           | H.265+ / H.265 / H.264+ / H.264                                                                                                                                                         |
| Bitrate:                            | max. 64 Mbps                                                                                                                                                                            |
| Supported hard drives:              | 1 x 6 TB SATA                                                                                                                                                                           |
| Recording modes:                    | Manual, Motion Detection, Schedule                                                                                                                                                      |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)                                                                                                                                          |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>1/4/9/16 channel synchronous playback |
| Network interface:                  | 1 x RJ-45 10/100/1000 Base-TX                                                                                                                                                           |
| Network functions:                  | Full support via network, Remote records copying, Web-Server built-in<br>max. 128 on-line users                                                                                         |
| Network protocols:                  | P2P, UPnP, DHCP                                                                                                                                                                         |
| ONVIF:                              | ✓                                                                                                                                                                                       |
| Default admin user / password:      | admin / 123456                                                                                                                                                                          |
| Default IP address:                 | DHCP or 192.168.1.30                                                                                                                                                                    |



# DATA SHEET

|                                  |                                                                                                                                                                    |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Web browser access ports:        | 80, 554                                                                                                                                                            |
| PC client access ports:          | Port no.: 80 or access by a cloud (P2P)                                                                                                                            |
| Mobile client access ports:      | 80                                                                                                                                                                 |
| Mobile phones support:           | Port no.: 80 or access by a cloud (P2P)<br>• Android: Free application <a href="#">BCS Manager</a><br>• iOS (iPhone): Free application <a href="#">BCS Manager</a> |
| RTSP URL:                        | rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream<br>rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream                                                |
| Alarm inputs / outputs:          | —                                                                                                                                                                  |
| PTZ control:                     | IP Speed Dome Cameras                                                                                                                                              |
| Motion Detection:                | ✓                                                                                                                                                                  |
| USB:                             | 2 x USB 2.0                                                                                                                                                        |
| Mouse support:                   | ✓                                                                                                                                                                  |
| IR remote controller in the set: | —                                                                                                                                                                  |
| Power supply:                    | 12 V DC / 2 A (power adapter included)                                                                                                                             |
| Power consumption:               | max. 3.2 W (without HDD)                                                                                                                                           |
| Weight:                          | 0.77 kg                                                                                                                                                            |
| Dimensions:                      | 260 x 243 x 46 mm                                                                                                                                                  |
| Supported languages:             | Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian                                                                                |
| Manufacturer / Brand:            | BCS BASIC                                                                                                                                                          |
| Guarantee:                       | <b>3 years</b>                                                                                                                                                     |