

Code: DS-KIS702Y

## VIDEO DOORPHONE KIT **DS-KIS702Y** Hikvision

Two-wire HIKVISION video doorphone system with 7" touch monitor and controller equipped with 4 2-wire buses. Video Doorphone is mounted in a surface housing.

The device has the ability to work with the [Hik-Connect](#) application for mobile devices.

The attached DS-KAD704Y controller also enables the connection of the video doorphone system to the LAN network and via it to the Internet.



Compatibility:	HIKVISION 2-wire - Y series
Doorbell button:	1 pcs
Sensor:	2.1 Mpx CMOS
Camera resolution:	1920 x 1080 - 1080p
Camera view angle:	146 °
Image compression method:	H.264
IR illuminator:	✓
Network protocols:	TCP/IP, RTSP, SIP
Alarm inputs:	4 pcs
Relay outputs:	2 x NO/NC
Main features:	<ul style="list-style-type: none"> <li>• True WDR - Wide Dynamic Range,</li> <li>• DNR - Digital Noise Reduction,</li> <li>• BLC - Back Light Compensation,</li> <li>• Motion Detection,</li> <li>• Bidirectional communication,</li> <li>• Microphone built-in,</li> <li>• Speakers built-in,</li> <li>• Noise suppression and echo cancellation,</li> <li>• Tamper detection - removing from mounting surface</li> </ul>
Power supply:	• 24 V DC - HIKVISION 2-wire
Power consumption:	< 4 W
Operation temp:	-40 °C ... 60 °C



# DATA SHEET

Housing:	Metal + Plastic
Color:	Black
"Index of Protection":	IP65
Weight:	0.38 kg
Dimensions:	100 x 98 x 44 mm

## INDOOR PANEL:

Compatibility:	HIKVISION 2-wire - Y series
Shield:	7 " - capacitive touch screen
Resolution:	1024 x 600
Internal memory:	128 MB (built-in)
Main features:	<ul style="list-style-type: none"><li>• Wi-Fi module - IEEE 802.11 b/g/n,</li><li>• Microphone built-in,</li><li>• Speakers built-in,</li><li>• Bidirectional communication,</li><li>• Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume,</li><li>• Automatically capture and save photos if there is no response to the bell button,</li><li>• IP Hikvision cameras support,</li><li>• The ability of direct communication between two or more panels,</li><li>• Register a short voice message if there is no response to the bell button</li><li>• Support for capturing a photo during video calls</li><li>• The microSD - max. 128 GB cards support - 16 GB included,</li><li>• The device is fully configurable via the <b>iVMS4200</b> software.</li><li>• In addition, the device has the ability to work with the <b>Hik-Connect</b> application on mobile devices</li></ul>
Controlling:	capacitive touch screen
Default administrator password:	— The administrator password should be set at the first start
Default password for securing the zone:	—
Alarm inputs:	8
Alarm outputs:	2
Power supply:	24 V DC - HIKVISION 2-wire
Power consumption:	≤ 4 W
Color:	Black + Silver
Operation temp:	-10 °C ... 50 °C
Weight:	0.32 kg
Dimensions:	200 x 140 x 25 mm

## ENCLOSURE:

Number of mounted modules:	1 pcs
Material:	Aluminum
Color:	Graphite
Weight:	0.22 kg

External dimensions:	117 x 107 x 37 mm
----------------------	-------------------

## Switch:

Number of ports:	6 x HIKVISION 2-wire ( 4 x device, 2 x Possibility to connecting in cascade ) , 1 x RJ-45
Compatibility:	HIKVISION 2-wire - Y series
Main features:	DIN, TS-35 rail mounting
Power supply:	24 V DC
Housing:	Plastic
Operation temp:	-10 °C ... 55 °C
Weight:	0.25 kg
Dimensions:	144 x 90 x 66 mm

## General information:

Supported languages:	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305303992
Guarantee:	<b>3 years</b>

