

## DATA SHEET

## Code: VTH5422HW-W INDOOR PANEL VTH5422HW-W IP / Wi-Fi / 2-Wire DAHUA



The VTH5422HW-W panel has been designed to create a simple and effective system of local communication.

The device works with video doorphones, and other DAHUA panels. It can be also used as simple alarm control panel, or notification module by the support 6 alarm inputs.

Attention! When selecting 2-wire devices, check the compatibility list available at the bottom of the page in the "files" section.

It is a hybrid module - it can work in a 2-Wire installation or as a standard IP video doorphone.

Compatibility:	DAHUA
Shield:	7 " capacitive touch screen
Resolution:	1024 x 600
Internal memory:	-
Memory card slot:	Micro SD memory cards up to 64GB support (possible local recording)
Main features:	<ul> <li>Wi-Fi module - 2.4 GHz IEEE 802.11 b/g/n,</li> <li>Protections : WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK,</li> <li>Microphone built-in,</li> <li>Speakers built-in,</li> <li>Bidirectional communication,</li> <li>Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume,</li> <li>The ability to automatically take and save photos if you do not answer to the bell button,</li> <li>The ability to record a short video message in the absence of a response to the bell button,</li> <li>IP Dahua cameras support ,</li> </ul>
Controlling:	capacitive touch screen
Alarm inputs:	6 (1 - as a bell)



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

VTH5422HW-W



## DATA SHEET

Alarm outputs:	1
Power supply:	<ul> <li>2-Wire IP interface,</li> <li>48 V DC / 1.25 A</li> </ul>
Power consumption:	• $\leq 6$ W (operation) • $\leq 2$ W (standby)
Operation temp:	-10 °C 55 °C
Color:	White
Weight:	0.36 kg
Dimensions:	189 x 130 x 26 mm
Supported languages:	Polish, English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years



VTH5422HW-W