

Code: SD22404DB-GNY-W

IP SPEED DOME CAMERA OUTDOOR **SD22404DB-GNY-W** Wi-Fi, - 4 Mpx 2.8 ... 12 mm DAHUA

IP camera equipped with very good high resolution sensor. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition.

The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m.

Thanks to the "Starlight" technology used, the camera only needs very low lighting to obtain a clear color image.



Standard:	TCP/IP
Sensor:	1/2.8 " STARVIS™ CMOS
Matrix size:	4 Mpx
Resolution:	2560 x 1440 - 4 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
IR illuminator:	—
Scanning system:	Progressive
Lens:	2.8 ... 12 mm
View angle:	• 90 ° ... 29 ° (manufacturer data) • 82 ° ... 28 ° (our tests result)
Optical zoom:	x 4
Digital zoom:	x 16
Min. illumination:	0.005 Lux (color) 0.0005 Lux (B/W)
S/N ratio:	> 55 dB
Preset rotation speed:	100 °/s (horizontal) 60 °/s (vertical)
Rotation speed (manual control):	• 0.1 °/s ... 100 °/s (horizontal) • 0.1 °/s ... 60 °/s (vertical)



DATA SHEET

Horizontal rotation range:	0 ° ... 355 ° - Rotation of the head is limited by stops
Vertical rotation range:	0 ° ... 90 °
RS-485 interface:	—
Number of presets:	300
Horizontal scan:	✓
Route settings:	8
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / H.264H / MJPEG
Audio:	—
Alarm inputs / outputs:	—
Main stream frame rate:	25 fps @ 4 Mpx
Network interface:	<ul style="list-style-type: none">• Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz• 10/100 Base-T (RJ-45)
Network protocols:	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, SAMBA, IEEE 802.1x
Memory card slot:	Micro SD memory cards up to 512GB support (possible local recording)
WEB Server:	Built-in
Max. number of on-line users:	20
ONVIF:	21.12
Mobile phones support:	Port 37777 <ul style="list-style-type: none">• Android: Free application DMSS• iOS (iPhone): Free application DMSS
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream





DATA SHEET

Main features:	<ul style="list-style-type: none">• D-WDR - Wide Dynamic Range• 2D-DNR, 3D-DNR - Digital Noise Reduction• F-DNR (Defog) - Reduction of image noise caused by precipitation• EIS - Electronic Image Stabilization• BLC - Back Light Compensation• HLC - High Light Compensation (spot)• Motion Detection• Configurable Privacy Zones• Day/night mode• ICR - Movable InfraRed filter• AGC - Automatic Gain Control• Sharpness - sharper image outlines• SMD 3.0 - searching for an object classified as: human, motor vehicle• IVS analysis, crossing the line (tripwire), intrusion - classification of people and vehicles, abandoned/missing object, detection of entry into the area / exit from the area, parking detection, fast moving, detection of people gathering, face detection - advanced face capture features
Power supply:	12 V DC / 400 mA
Power consumption:	≤ 4.8 W
Housing:	Speed Dome, Metal
Color:	White
Operation temp:	-30 °C ... 60 °C
"Index of Protection":	IP66
Vandal-proof:	IK10
Weight:	0.57 kg
Dimensions:	Ø 122 x 89 mm
Supported languages:	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years