

Code: DS-KAD706Y

## SWITCH **DS-KAD706Y** FOR HIKVISION 2-WIRE VIDEO DOORPHONE SYSTEMS

The device has 6 2-wire buses for connecting the monitors and external panels (power supply and signal transmission) and 1 Ethernet socket for connecting the LAN network. In addition, one of the ports is adapted to power an extensive gate station with a maximum power consumption of 16W. In addition, the switch is equipped with additional 2-wire bus outputs for cascading connection with DS-KAD706Y / DS-KAD706Y-S.

The switch can also be connected to the LAN network, which allows access to the gate opening and the option of receiving a call from the video doorphone via the mobile application. When connecting a cascade of devices to the LAN network, it is recommended to connect the DS-KAD706Y-S switch to it.



Number of ports:	6 x HIKVISION 2-wire ( 1 x max. 16 W ) , 2 x HIKVISION 2-wire - Uplink 1 x RJ-45
Compatibility:	HIKVISION 2-wire - Y series
Main features:	<ul style="list-style-type: none"> <li>• Possibility to connecting in cascade</li> <li>• DIN, TS-35 rail mounting</li> </ul>
Power supply:	24 V DC
Power consumption:	< 6 W - CH1 ... CH5 < 16 W - CH6
Housing:	Plastic
Operation temp:	-10 °C ... 55 °C
Weight:	0.27 kg
Dimensions:	144 x 90 x 66 mm
SAP Code:	305303644
Manufacturer / Brand:	Hikvision
Guarantee:	<b>3 years</b>