

Code: HT-6889

TEMPERATURE METER **HT-6889** -50 °C ... 2200 °C



The HT-6889 pyrometer allows for accurate, non-contact measurement of the object's temperature.

Attention! The device is not intended for medical use.

Temperature measurement range:	-50 °C ... 2200 °C
Accuracy of temperature measurement:	<ul style="list-style-type: none"> • ≤ -23 °C : ± 7 °C, • -23 °C ... -2 °C : ± 4 °C • -2 °C ... 94 °C : ± 2.5 °C • 94 °C ... 1000 °C : ± 1 °C • > 1000 °C : ± 2 °C
Measurement resolution:	<ul style="list-style-type: none"> • 0.1 °C @ ≤ 1000 °C, • 1 °C @ > 1000 °C
Response time:	100 ms
Spectral range:	8 μ m ... 14 μ m
Main features:	<ul style="list-style-type: none"> • Built-in laser pointer, • Memory of the last 100 measurements • Selectable measurement unit: °C / °F • Automatic sleep mode after 7 s idle time • Low battery indicator • Probe • White backlight
Power supply:	9V, type 6F22 battery (not included)
Housing:	Plastic



DATA SHEET

Color:	Yellow + Black
Operation temp:	0 °C ... 50 °C
Permissible relative humidity:	< 90 %
Dimensions:	125 x 224 x 52 mm
Weight:	0.25 kg
Manufacturer / Brand:	Hti
Guarantee:	2 years