

Code: DS-3E0505HP-E

SWITCH POE **DS-3E0505HP-E** 4-PORT Hikvision

Due to reliability and ensuring high quality of transmission, the DS-3E0505HP-E 4-port PoE desktop type switch is perfect solution for expanding home or office network.

When the Extend function is enabled the PoE range increases up to 300m and the transmission speed reduces to 10 Mb/s.



LAN ports:	• 4 x RJ45 10/100/1000 Base-TX (1 x Hi-PoE (802.3af/at/bt) + 3 x PoE (802.3af/at)), • 1 x RJ45 10/100/1000 Base-TX - Uplink
Transmission speed:	• 10 / 100 / 1000 Mbps - 4 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 1 Port Uplink
Maximal output power:	• 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 4 ports
Maximal total power:	60 W
MAC addresses table:	2k
Management:	—
Operation modes:	• Extend Off : 100 m, 1000 Mbps - 1 ... 4 ports • Extend On : 300 m, 10 Mbps - 3, 4 ports • Port Isolation : 1 ... 4 ports • Watchdog PoE : 1 ... 4 ports
LED diodes:	Power, Link/Act, PoE, PoE Max
Main features:	• MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Overvoltage protection : 6 kV - PoE ports • EXTEND mode - 7, 8 ports • Power supply PoE : wires : 1-2, 3-6, 4-5, 7-8 - 1 ... 4 ports • Port isolation • PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • Kensington-lock compatible
Certificates:	CE, FCC, RoHS
Housing:	Metal
Power supply:	48 V DC / 1.36 A (power adapter included)



DATA SHEET

Power consumption:	max. 65 W
Operation temp:	-10 °C ... 40 °C
Weight:	0.26 kg
Dimensions:	121 x 88 x 28 mm
Manufacturer / Brand:	Hikvision
SAP Code:	301801511
Guarantee:	3 years