

Code: DS-3E0510HP-E

## SWITCH POE **DS-3E0510HP-E** 8-PORT SFP Hikvision

Due to reliability and ensuring high quality of transmission, the DS-3E0510HP-E 10/100/1000M 8-port PoE desktop type switch is perfect solution for expanding home or office network.

When the Extend function is enabled the PoE range increases up to 300m and the transmission speed reduces to 10 Mb/s.

Attention! The SFP port requires the SFP module, which is available in our offer.



LAN ports:	<ul style="list-style-type: none"> <li>• 8 x RJ45 10/100/1000 Base-TX ( 2 x Hi-PoE (802.3af/at/bt) + 6 x PoE (802.3af/at) ),</li> <li>• 1 x RJ45 10/100/1000 Base-TX - Uplink,</li> <li>• 1 x port SFP 1000 Base-X - Uplink</li> </ul>
Transmission speed:	<ul style="list-style-type: none"> <li>• 10 / 100 / 1000 Mbps - 8 LAN &amp; PoE ports,</li> <li>• 10 / 100 / 1000 Mbps - 1 Port RJ45 (Uplink),</li> <li>• 1000 Mbps - 1 Port SFP (Uplink)</li> </ul>
Maximal output power:	<ul style="list-style-type: none"> <li>• 90 W / port Hi-PoE - 1, 2 ports</li> <li>• 30 W / port PoE - 3 ... 8 ports</li> </ul>
Maximal total power:	110 W
MAC addresses table:	4k
Management:	—
Operation modes:	<ul style="list-style-type: none"> <li>• Extend Off : 100 m, 1000 Mbps - 1 ... 8 ports</li> <li>• Extend On : 300 m, 10 Mbps - 7, 8 ports</li> <li>• Port Isolation : 1 ... 8 ports</li> <li>• Watchdog PoE : 1 ... 8 ports</li> </ul>
LED diodes:	Power, Link/Act, PoE, PoE Max
Main features:	<ul style="list-style-type: none"> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Overvoltage protection : 6 kV - PoE ports</li> <li>• EXTEND mode - 7, 8 ports</li> <li>• Power supply PoE : <ul style="list-style-type: none"> <li>- wires : 1-2, 3-6 - 3 ... 6 ports</li> <li>- wires : 1-2, 3-6, 4-5, 7-8 - 1, 2, 7, 8 ports</li> </ul> </li> <li>• Port isolation</li> <li>• PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li> <li>• Kensington-lock compatible</li> </ul>
Certificates:	CE, FCC, RoHS
Housing:	Metal





# DATA SHEET

Power supply:	54 V DC / 2.22 A (power adapter included)
Power consumption:	max. 120 W
Operation temp:	-10 °C ... 40 °C
Weight:	0.58 kg
Dimensions:	218 x 109 x 28 mm
Manufacturer / Brand:	Hikvision
SAP Code:	301801513
Guarantee:	<b>3 years</b>