

Code: DS-3T0506HP-E/HS

SWITCH POE **DS-3T0506HP-E/HS** 4-PORT SFP Hikvision

Due to reliability and ensuring high quality of transmission, the DS-3T0506HP-E/HS 10/100/1000 Mb/s 4-port PoE desktop type switch is perfect solution for expanding home or office network. 4 ports support the Power over Ethernet (PoE) function.

DS-3T0506HP-E/HS is designed to mount on the DIN 35 mm rail.



LAN ports:	• 4 x RJ45 10/100/1000 Base-TX (1 x Hi-PoE (802.3af/at/bt) + 3 x PoE (802.3af/at)), • 2 x port SFP 1000 Base-X - Uplink
Transmission speed:	• 10 / 100 / 1000 Mbps - 4 LAN & PoE ports, • 1000 Mbps - 2 SFP (Uplink) ports
Maximal output power:	• 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 4 ports
Maximal total power:	60 W
MAC addresses table:	2k
Management:	—
Operation modes:	• Extend Off : 100 m, 1000 Mbps - 1 ... 4 ports • Extend On : 300 m, 10 Mbps - 3, 4 ports • Port Isolation : 1 ... 4 ports • Watchdog PoE : 1 ... 4 ports
LED diodes:	Power, Link/Act, PoE, PoE Max, SFP - 5, 6 ports
Main features:	• MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Overvoltage protection : 6 kV - PoE ports • EXTEND mode - 3, 4 ports • The device supports 8-pin power supply : wires 1-2, 3-6, 4-5, 7-8 • Port isolation • PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected
Certificates:	CE, FCC, RoHS
Housing:	Metal
Power supply:	48 V DC / 1.35 A (power adapter included)



DATA SHEET

Power consumption:	max. 65 W
Operation temp:	-30 °C ... 65 °C
Weight:	0.36 kg
Dimensions:	158 x 104 x 32 mm
Manufacturer / Brand:	Hikvision
SAP Code:	301801602
Guarantee:	3 years