

## DATA SHEET

Code: TEDEE-GO/GC

## SMART DOOR LOCK **TEDEE-GO/GC** Bluetooth, Tedee GERDA

The smart lock allows you to remotely open the door to your home, apartment or business.

The TEDEE-GO/GC lock is mounted on the existing door lock - without the need to replace the cylinder and keys. The TEDEE-GO/GC simply electronically turns a regular key in the lock. You don't have to replace anything, and you can always use your key to open the door from the outside. Easy and quick installation on the inside of the door makes the lock invisible to outsiders.

It is possible to operate the device from the mobile application on the Android, iOS systems via the Bluetooth / Wi-Fi - Tedee Bridge connection. For the proper management of the device, it is necessary to install the Tedee mobile application. Tedee application works perfectly with Google Assistant, Amazon Alexa, Apple Siri and many others, which allows you to control connected devices using voice commands. It provides features such as remote operation, notifications, activity log, auto-open. The TEDEE-GO/GC smart lock is compatible with over 15 smart home systems (e.g. Apple HomeKit). To use these features, your TEDEE-GO/GC device must be paired with the smart Tedee Bridge connected to the internet. When paired with the Tedee Keyboard, the lock can be opened with a PIN code.

**Attention!** The TEDEE-GO/GC lock is designed to work with a European lock cylinder only, for other types an adapter is additionally required (included in the set). Please ensure that your current lock cylinder has the emergency function before purchasing.



Application:	opening and closing the lock
Compatible lock type:	European cylinder with emergency function     Adapter available : Nordic, American
Wireless:	Bluetooth, 2.4 GHz - BLE 5.0
Mobile phones support:	The <u>Tedee</u> free application on Android     The <u>Tedee</u> free application on iOS



## DATA SHEET

	Remote control and management - Tedee application :
Main features:	- remote access,
	- Phone notification, - Activity log,
	- auto-open and close,
	- Setting scenarios by different events,
	<ul> <li>voice control</li> <li>Bi-directional encrypted radio communication : TLS 1.3</li> </ul>
	Secure virtual key - 256-bit data encryption
	Remote opening of the door
	• lock button
	Opening the door : manual, lock button, Tedee application     3 levels of access, password-protected
	Compatibility with many smart home systems (e.g. Apple HomeKit, Google
	Assistant, Amazon Alexa, Homey, Fibaro, Grenton, eeDomus, Consolomio)  • LED indication
	Full compatibility with inward-opening doors
	Compatibility with outward-opening doors : min. 40 mm (the distance between the
	cylinder axis and the door frame)
Power supply:	3 x Battery CR123A 3 V (included)
Backup time:	6 8 months
Housing:	Plastic (ABS)
"Index of Protection":	IP20
Color:	Graphite + Black
Operation temp:	10 °C 40 °C
Permissible relative humidity:	max. 65 %
Weight:	0.232 kg
Dimensions:	Ø 58 x 65 mm
Manufacturer / Brand:	GERDA / Tedee
Guarantee:	2 years