

Code: APTI-W22C4G-TUYA

IP CAMERA **APTI-W22C4G-TUYA** Tuya Smart 4G/LTE - 1080p 3.6 mm

The cameras cooperating with the user-friendly Tuya platform have been designed with special care to simplify the configuration process and enable the user to create a simple and effective monitoring system.

The camera works with the 4G/LTE network and the connection is made on a plug and play basis - just install a nanoSIM card and the device will establish an Internet connection by itself - this solution allows the camera to be used wherever there is an operator network coverage. Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera.

Attention! Devices cooperating with the Tuya platform do not have a WEB interface. The camera works only with the mobile application (the camera does not work with recorders). Controlling the device and schedule settings is possible if the device has access to the Internet.



| | |
|---------------------------|--|
| Standard: | TCP/IP |
| Sensor: | 1/2 " Progressive Scan CMOS |
| Matrix size: | 2.1 Mpx |
| Resolution: | 1920 x 1080 - 1080p |
| Lens: | 3.6 mm |
| View angle: | • 99 ° (manufacturer data) |
| Range of IR illumination: | 15 m |
| Audio: | <ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Audio transmission via network, • Bi-directional audio streaming support |
| Image compression method: | H.265 |
| Network protocols: | TCP/IP, P2P |
| Network interface: | 4G LTE |
| ONVIF: | — |



DATA SHEET

| | |
|---|--|
| WEB Server: | — |
| Mobile phones support: | Access by a cloud (P2P) <ul style="list-style-type: none">• The Tuya Smart free application on Android• The Tuya Smart free application on iOS |
| Default IP address: | DHCP |
| Web browser access ports: | — |
| PC client access ports: | — |
| Mobile client access ports: | — |
| Port ONVIF: | — |
| RTSP URL: | — |
| Memory card slot: | Micro SD memory cards up to 128GB support (possible local recording) |
| Main features: | <ul style="list-style-type: none">• 4G LTE support• WDR - Wide Dynamic Range• BLC/HLC - Back Light / High Light Compensation• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect• Day/night mode• ICR - Movable InfraRed filter• Motion Detection - Built-in PIR detector• USB C interface• RESET button |
| Battery operation time: | max. 60 days |
| Charging time (recover to 100% capacity): | 6 h from USB port |
| Power supply: | <ul style="list-style-type: none">• 4 x Li-Ion battery ICR18650 - 3.7 V / 2600 mAh (included),• Solar Panel : 1.6 W,• 5 V DC - micro USB socket (power adapter not included) |
| Housing: | Metal |
| "Index of Protection": | IP66 |
| Weight: | <ul style="list-style-type: none">• 0.8 kg• 0.94 kg (with bracket) |
| Dimensions: | <ul style="list-style-type: none">• 200 x 96 x 67 mm• 305 x 96 x 125 mm (with bracket) |
| Operation temp: | -30 °C ... 60 °C |
| Supported languages: | English |
| Manufacturer / Brand: | APTI |
| Guarantee: | 2 years |