

Code: BCS-L-NVR6404-A-4K

NVR **BCS-L-NVR6404-A-4K** 64 CHANNELS + eSATA BCS Line

The BCS-L-NVR6404-A-4K digital recorder is a professional device using in IP surveillance systems.



| | |
|-------------------------------------|--|
| Standard: | IP |
| Supported resolutions: | max. 32 Mpx |
| Video outputs: | 2 pcs HDMI 4K 2 pcs VGA |
| Audio support: | 64 Channels - Audio from cameras |
| Audio inputs: | 1 pcs CINCH |
| Audio outputs: | 2 pcs CINCH |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| Bitrate: | max. 384 Mbps |
| Supported hard drives: | <ul style="list-style-type: none"> • 4 x 16 TB SATA + eSATA • Possibility of operation the disks in RAID 0/1/5/6/10 array |
| Recording modes: | Manual, Sensor, Motion detection, Schedule |
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |
| Searching and playback the records: | <ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • 1/4/9/16 channel synchronous playback |
| Network interface: | 2 x RJ-45, 10/100/1000 Base-TX |
| Network functions: | <ul style="list-style-type: none"> • Live image view, Playback the records, Backup the records, remote access, CMS application • Web-Server built-in, 128 on-line users |
| ONVIF: | ✓ |
| Default IP address: | 192.168.1.108 |
| Default admin user / password: | admin / - The administrator password should be set at the first start |



DATA SHEET

| | |
|----------------------------------|---|
| Mobile phones support: | Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application BCS Manager• iOS (iPhone): Free application BCS Manager |
| Web browser access ports: | 80, 37777 |
| PC client access ports: | 37777 |
| Mobile client access ports: | 37777 |
| RTSP URL: | <ul style="list-style-type: none">• rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream• rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream |
| USB: | <ul style="list-style-type: none">• 1 pcs USB 2.0• 2 pcs USB 3.0 |
| Serial ports: | RS-485, RS-232 |
| Alarm inputs / outputs: | 16 / 6 |
| PTZ control: | <ul style="list-style-type: none">• IP Speed Dome Cameras• RS-485 |
| Motion Detection: | ✓ |
| Intelligent image analysis: | ✓ |
| Main features: | <ul style="list-style-type: none">• Intelligent image analysis : 10 rules - object detection (people, vehicle)• face detection• Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask)• Face recognition• Support for up to 20 face databases, including 20 000 face images• SMD PLUS - searching for an object classified as: human, motor vehicle• Cooperation with POS (Point of Sale) terminals - POSNET <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none">• ANPR• Authorized and unauthorized license plate lists: up to 20 000 records• counting people / vehicles• crowd gathering estimation• heat map• metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles) |
| Mouse support: | ✓ |
| IR remote controller in the set: | — |
| Switch PoE: | — |
| Power supply: | 100 ... 240 V AC |
| Power consumption: | max. 13 W (without HDD) |
| Operation temp: | -10 °C ... 55 °C |
| Weight: | 4.46 kg |
| Dimensions: | 440 x 413 x 76 mm |



DATA SHEET

| | |
|-----------------------|-----------------|
| Supported languages: | Polish, English |
| Manufacturer / Brand: | BCS Line |
| Guarantee: | 3 years |

