

Code: CS4006-4ET-60

## SWITCH POE **CS4006-4ET-60** 4-PORT DAHUA

Due to reliability and ensuring high quality of transmission, the CS4006-4ET-60 10/100 Mb/s 4-port PoE desktop type switch is perfect solution for expanding home or office network. Four ports support Power over Ethernet (PoE) function.

Switch is managed through the web and the cloud (DoLink Care application).



|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAN ports:            | <ul style="list-style-type: none"> <li>• 4 x RJ45 10/100 Base-T ( 1 x Hi-PoE + 3 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 10/100/1000 Base-T - Uplink</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Transmission speed:   | <ul style="list-style-type: none"> <li>• 10 / 100 Mbps : 4 LAN &amp; PoE ports,</li> <li>• 10 / 100 / 1000 Mbps : 2 Uplink ports</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Maximal output power: | <ul style="list-style-type: none"> <li>• 60 W / port Hi-PoE - Port 1</li> <li>• 30 W / port PoE 802.3af/at - 2 ... 4 ports</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Maximal total power:  | 60 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| MAC addresses table:  | 8k                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Management:           | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Operation modes:      | Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| LED diodes:           | Power, System, PoE, Link/Act                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Main features:        | <ul style="list-style-type: none"> <li>• Switch is managed through the web and the cloud (DoLink Care application)</li> <li>• PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-)</li> <li>• Intelligent management of Power Supply Unit power's output stage</li> <li>• protection against lightning discharges and voltage differences and strokes between devices</li> <li>• Watchdog PoE</li> <li>• Loop Protection</li> <li>• Compliance with the LLDP protocol</li> <li>• Port Based VLAN : 32</li> <li>• Data Flow Control (802.3x)</li> <li>• DHCP client</li> <li>• RESET button</li> <li>• Kensington Lock</li> <li>• Possibility to mount to the wall</li> </ul> |
| Certificates:         | CE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Protections:          | <ul style="list-style-type: none"> <li>• Protection against lightning discharges (common/differential) : 4 / 2 kV</li> <li>• Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |



## DATA SHEET

|                       |                                           |
|-----------------------|-------------------------------------------|
| Housing:              | Desktop, Metal                            |
| Power supply:         | 53 V DC / 1.22 A (power adapter included) |
| Power consumption:    | max. 65 W                                 |
| Operation temp:       | -10 °C ... 55 °C                          |
| Weight:               | 0.29 kg                                   |
| Dimensions:           | 130 x 85 x 26 mm                          |
| Manufacturer / Brand: | DAHUA                                     |
| Guarantee:            | <b>3 years</b>                            |