

Code: APTI-N1611-8P-I3

NVR **APTI-N1611-8P-I3** 16 CHANNELS, 8 PoE

The APTI-N1611-8P-I3 digital recorder is a professional device applicable in surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



| | |
|----------------------------------|--|
| Standard: | TCP/IP |
| Supported resolutions: | max. 8 Mpx - 3840 x 2160 px, 4K UHD |
| Video outputs: | 1 pcs HDMI 4K 1 pcs VGA |
| Audio support: | <ul style="list-style-type: none"> • 16 Channels - Audio from cameras • Bi-directional audio streaming support |
| Audio inputs: | 1 pcs CINCH |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 |
| Bitrate: | 120 Mbps |
| Supported hard drives: | 1 x 8 TB SATA |
| Recording modes: | Manual, Sensor, Motion detection, Schedule |
| External storage devices backup: | Records backup at (.avi) format to USB (pendrive) |
| Search for recordings: | Records searching: timeline or file list. Playback: forward, fast |
| Playback the records: | 1 x 8 Mpx / 2 x 5 Mpx / 4 x 1080p |
| Network interface: | 1 x RJ-45 10/100/1000 Base-TX |
| Network functions: | Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters |
| Network protocols: | IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE |
| ONVIF: | ✓ |
| Default IP address: | 192.168.1.88 |
| Default admin user / password: | admin / 12345 |



DATA SHEET

| | |
|----------------------------------|---|
| Mobile phones support: | Access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application BitVision, Android: Free application iVMS320• Android: Free application BitVision, iOS: Free application iVMS320 |
| Web browser access ports: | 80, 5000, 554 |
| PC client access ports: | 80, 5000, 554 |
| USB: | 2 pcs USB 2.0 |
| Serial ports: | — |
| Alarm inputs / outputs: | 4 / 1 |
| PTZ control: | IP Speed Dome Cameras |
| Motion Detection: | Split the screen into zones : 22 x 18 motion zones |
| Intelligent image analysis: | ✓ |
| Main features: | <ul style="list-style-type: none">• Support for intelligent image analysis, available in cameras from the APTI-AI series• D-ZOOM - Digital Zoom |
| Mouse support: | ✓ |
| IR remote controller in the set: | — |
| Switch PoE: | 8-port PoE Switch built-in, 15 W / Channel, PoE (802.3af) |
| Maximum total switch load: | 72 W |
| Power supply: | 48 V DC / 2.5 A (power adapter included) |
| Power consumption: | ≤ 10 W (without HDD & PoE) |
| Operation temp: | -10 °C ... 50 °C |
| Weight: | 0.98 kg |
| Dimensions: | 260 x 237 x 45 mm |
| Supported languages: | Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Ukrainian, Italian |
| Manufacturer / Brand: | APTI |
| Guarantee: | 2 years |