

Code: DS-7108NI-Q1(D)

NVR **DS-7108NI-Q1(D)** 8 CHANNELS Hikvision

The DS-7108NI-Q1(D) digital recorder is a professional device using in IP surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.



| | |
|-------------------------------------|---|
| Standard: | TCP/IP |
| Supported resolutions: | max. 6 Mpx |
| Video outputs: | 1 pcs HDMI 1 pcs VGA |
| Audio support: | 8 Channels - Audio from cameras |
| Audio inputs: | — |
| Audio outputs: | — |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 |
| Supported hard drives: | 1 x 6 TB SATA |
| Recording modes: | Manual, Motion Detection, Schedule |
| Network protocols: | TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP |
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow |
| Bitrate: | max. 60 Mbps |
| Network functions: | Live image view, Playback the records, Backup the records |
| ONVIF: | ✓ |
| Mobile phones support: | Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect |
| Default admin user / password: | admin / - The administrator password should be set at the first start |





DATA SHEET

| | |
|----------------------------------|--|
| Default IP address: | 192.168.1.64 |
| Web browser access ports: | 80 |
| PC client access ports: | Port no.: 8000 or access by a cloud (P2P) |
| Mobile client access ports: | 8000 |
| RTSP URL: | <ul style="list-style-type: none">• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream |
| Alarm inputs / outputs: | — |
| PTZ control: | IP Speed Dome Cameras |
| Motion Detection: | ✓ |
| Intelligent image analysis: | ✓ |
| USB: | 2 pcs USB 2.0 |
| Mouse support: | ✓ |
| IR remote controller in the set: | — |
| Operation temp: | -10 °C ... 55 °C |
| Power supply: | 12 V DC / 1.5 A (power adapter included) |
| Weight: | 0.43 kg |
| Dimensions: | 200 x 203 x 48 mm |
| Supported languages: | Polish, English |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 303618111 |
| Guarantee: | 3 years |

