

Code: IDS-E04HQHI-D

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **IDS-E04HQHI-D** 4 CHANNELS ACUSENSE Hikvision

The IDS-E04HQHI-D digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), IP - Hikvision and PAL interface is a professional device applicable in surveillance systems. The recorder supports AcuSense technology, allowing to filter false alarms based on the recognition of people and vehicles.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.

Attention! The recorder has a factory-installed eSSD drive, without the possibility of replacing or increasing the amount of memory available for recordings. The storage time for recordings for 4 analog cameras, specified by the manufacturer, is 4 weeks.



Standard:	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs:	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	4 - Audio support via coaxial cable
Audio outputs:	—
Image compression method:	H.265+ / H.265
Image records resolutions:	• HD-TVI : 3K Lite - 1480 x 1665 , 5M-N - 1296 x 1944 , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • AHD / HD-CVI : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • CVBS : 960H - 960 x 576 , • IP : max. 6 Mpx - 3072 x 2048



DATA SHEET

Recording speed adjustment:	6 Mpx IP @ 1 ... 25 fps 5M-N @ 1 ... 12 fps 3K Lite @ 1 ... 12 fps 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Operation modes:	• 4 x HD-TVI / AHD / HD-CVI / PAL + 1 x IP
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 1024 GB eSSD - Built-in, Space available for records : 960 GB
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time
Network interface:	1 x RJ-45 - 10/100 Base-T
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols:	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, UPnP, HTTPS
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS (iPhone): Free application Hik-Connect
Default IP address:	DHCP or 192.168.1.64
Default admin user / password:	admin / -
Web browser access ports:	80
PC client access ports:	554 RTSP, 8000
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs:	—
PTZ control:	Control compatible with coax HD-TVI Hikvision
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Main features:	• DVR from the AcuSense series • Intelligent image analysis - Deep Learning technology • Smart motion detection (with recognizing people and vehicles) • Filtering of false alarms based on the recognition of persons and vehicles
USB:	2 pcs USB 2.0
Mouse support:	✓
IR remote controller in the set:	—



DATA SHEET

Power supply:	12 V DC / 1 A (power adapter included)
Color:	Black
Weight:	0.42 kg
Dimensions:	152 x 122 x 46 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	300228635
Guarantee:	3 years