

Code: RG-ES226GC-P

SWITCH POE **RG-ES226GC-P** 24-PORT REYEE

Due to the reliability and ensuring high quality of transmission, the RG-ES226GC-P 24-port PoE switch is an ideal solution for applications in CCTV IP installations. 24 ports support the Power over Ethernet (PoE) function.

Switch is managed through the web and the cloud (Ruijie Reyee application).



LAN ports:	<ul style="list-style-type: none"> • 24 x RJ45 10/100/1000 Base-T (24 x PoE (802.3af/at)), • 2 x port SFP 1000 Base-X - Uplink
Management:	✓
Number of fan coolers:	1 pcs
LED diodes:	STATUS indicator, PoE, Link/Act
Transmission speed:	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 24 LAN & PoE ports • 1000 Mbps : 2 SFP ports
Maximal total power:	370 W
Switching performance:	52 Gb/s
Packet redirection speed:	38.69 Mpps
MAC addresses table:	8k
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Default IP address:	10.44.77.200
Operation modes:	<ul style="list-style-type: none"> • Flow Control ON - Data flow control is enabled and all ports can communicate with each other, • Flow Control OFF - Data flow control is disabled and all ports can communicate with each other, • Port Isolation
Main features:	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (Ruijie Reyee application) • Can be mounted in a Rack cabinet, • Supports up to 16 VLANs at the same time (for 4K ID VLAN addresses) • DHCP client • DHCP snooping support • Port mirroring function • Loop Protection • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200.000 h
Certificates:	CE, RoHS
Protections:	Protection against lightning discharges : 4 kV



DATA SHEET

Housing:	Desktop, Metal
Power supply:	100 ... 240 V AC
Power consumption:	≤ 443 W
Operation temp:	0 °C ... 40 °C
Weight:	4.02 kg
Dimensions:	440 x 295 x 45 mm
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	3 years