

Code: RG-NBS5200-24SFP/8GT4XS

Switch SFP **RG-NBS5200-24SFP/8GT4XS** 24-PORT REYEE

The RG-NBS5200-24SFP/8GT4XS switch is designed for large streams of video data in the CCTV IP surveillance networks.



LAN ports:	• 24 x SFP ports • 8 x (RJ45) 10/100/1000 Mbps • 4 x SFP+ ports
Management:	✓
Transmission speed:	• 1000 Mbps - 24 x SFP ports • 10/100/1000 Mbps - 8 x Gigabit Ethernet • 10 Gb/s - 4 x port SFP+
Switching performance:	128 Gb/s
Packet redirection speed:	96 Mpps
MAC addresses table:	16k
Certificates:	CE, RoHS
Number of fan coolers:	1
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Jumbo Frame:	9 kB
Default IP address:	10.44.77.200



DATA SHEET

Main features:	• Can be mounted in a Rack cabinet • Switch is managed through the web and the cloud (Ruijie Reyee application) • Access Control List - ACL package filtering based on source and destination IP addresses • IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs • DHCP client • BPDU Filtering/Guard • Loop back detection • Spanning Tree STP/RSTP • Errdisable Recovery • Up to 16 aggregation groups and up to 8 ports per group • IGMP Snooping V1/V2/V3 • DHCP snooping support • Port mirroring function • Loop Protection • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200.000 h
Operation temp:	0 °C ... 50 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Protections:	Protection against lightning discharges : 6 kV
Power supply:	100 V ... 240 AC
Power consumption:	≤ 42 W
Weight:	3.59 kg
Dimensions:	440 x 267 x 63 mm
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	5 years