

Code: RG-AP680(CD)

ACCESS POINT **RG-AP680(CD)** Wi-Fi 6, SFP 2.4 GHz, 5 GHz, 547 Mbps + 1201 Mbps RUIJIE

The RG-AP680(CD) access point broadcasts 2 separate wireless networks in the 5 GHz band with speed 1201 Mb/s and in the 2.4 GHz band with speed 574 Mb/s.

The Access Point is designed for outdoor use, ensuring good connectivity in extreme weather environments over longer distances.

Supports 802.11ax standard - the next generation of Wi-Fi.

Access Point is managed through the web and the cloud (Ruijie Reyee application).



Frequency range:	<ul style="list-style-type: none"> • 2.4 GHz (2.4 ... 2.4835 GHz), • 5 GHz (5.150 ... 5.250, 5.250 ... 5.350, 5.470 ... 5.725, 5.725 ... 5.850 GHz) ,
Antenna type:	2x2 MU-MIMO - embedded <ul style="list-style-type: none"> • 9 dBi @ 2.4 GHz • 9 dBi @ 5 GHz
Standards:	<ul style="list-style-type: none"> • IEEE 802.11 b/g/n/ax @ 2.4 GHz, • IEEE 802.11 a/n/ac/ax @ 5 GHz
Baud rates:	547 Mbps @ 2.4 GHz + 1201 Mbps @ 5 GHz
LAN ports:	<ul style="list-style-type: none"> • 1 x 10 / 100 / 1000 Mbps Ethernet + PoE IN - RJ45, • 1 x 1000 Mbps - SFP
Port USB:	—
LED indicators:	Power / System, 3 x Signal indicator
DDNS:	—
DHCP server:	✓
Firmware update:	✓





DATA SHEET

Protections:	<ul style="list-style-type: none">• WEP 64/128-bit, WPA-TKIP, WPA-PSK, WPA2 AES• IEEE 802.1x and Radius Authentication• Black list• Access Control List - ACL package filtering based on source and destination MAC addresses• CPP• NFPP• SSID hiding
Operation modes:	Access Point
Management interface:	<ul style="list-style-type: none">• Ruijie Cloud Central Management System• Configuration using the Ruijie Reyeeye application• Remote management• Web browser• Console - RJ-45 output
Mobile phones support:	Android: Free application Ruijie Reyeeye iOS (iPhone): Free application Ruijie Reyeeye
Default IP address:	192.168.110.1
Transmitter power:	max. 28 dBm @ 2.4 GHz max. 28 dBm @ 5 GHz
Main features:	<ul style="list-style-type: none">• Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments• OFDMA• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network• Load balance• WLAN : 32 x BSSID - 16 x Wireless BSSID• Multicast• IPv4/IPv6• ICMP - Static routing• VPN support : IPsec, PPPoE• SNMP• Statistical Reporting, System logs• DHCP client• Bluetooth 5.0 interface• RESET button• Signal indicator• Industrial wide temperature design.• Overvoltage protection : 9 kV
Housing:	Plastic, hermetic
"Index of Protection":	IP68
Power supply PoE:	PoE (802.3af/at)
Power supply:	<ul style="list-style-type: none">• 48 V DC / 0.35 A (not included)• PoE / PoE+
Power consumption:	max. 12.95 W
Operation temp:	-40 °C ... 65 °C
Permissible relative humidity:	0 % ... 100 % (non-condensing)
Weight:	<ul style="list-style-type: none">• 1.2 kg (without bracket)
Dimensions:	251 x 168 x 64 mm (without bracket)
Manufacturer / Brand:	RUIJIE
Guarantee:	3 years