

Code: HN-C32/3

## CIRCUIT BREAKER **HN-C32/3** THREE-PHASE 32 A C TYPE EATON

Thermal-magnetic circuit breaker with C-type curve and 32A rated current. The HN-C32/3 circuit breaker is compatible to DIN TS-35 rail mounting system.

Circuit breakers with C-type breaking curve are designed to protection against short-circuits and overloads of the installation, where are used the devices with high inrush currents (motors, transformers).



Device type:	Circuit Breaker, Three-phase
Rated current:	32 A
Number of poles:	3
Tripping curves:	C type
Breaking capacity:	6000 A
Rated voltage:	<ul style="list-style-type: none"> <li>• 230 V AC / 50 Hz</li> <li>• 400 V AC / 50 Hz</li> </ul>
Connectors type:	screw terminals
Wire gauge:	1 mm <sup>2</sup> - 25 mm <sup>2</sup>
Main features:	<ul style="list-style-type: none"> <li>• Contact position indicator</li> <li>• Possibility of sealing</li> </ul>
Housing:	Plastic, DIN, TS-35 rail mounting
Width in 17.5 mm modules:	3
Weight:	0.320 kg



# DATA SHEET

---

Dimensions:	52.5 x 84.5 x 73 mm
Manufacturer / Brand:	EATON
Guarantee:	2 years

