

Code: NSW2020-24T1GT1GC-POE-IN

## SWITCH POE **NSW2020-24T1GT1GC-POE-IN** 24-PORT SFP UNIVIEW

Due to the reliability and ensuring high quality of transmission, the NSW2020-24T1GT1GC-POE-IN 24-port PoE switch is an ideal solution for applications in CCTV IP installations. 24 ports support Power over Ethernet (PoE) function.



LAN ports:	<ul style="list-style-type: none"> <li>• 24 x RJ45 ( 24 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 - Uplink,</li> <li>• 1 x Combo: RJ45/SFP - Uplink</li> </ul>
Management:	—
LED diodes:	G1/SFP1, G2, PoE Max, Power, Link/Act, PoE
Transmission speed:	<ul style="list-style-type: none"> <li>• 100 Mbps : 24 LAN &amp; PoE ports,</li> <li>• 1000 Mbps : 2 LAN ports - Uplink,</li> <li>• 1000 Mbps : 1 Port SFP - Uplink</li> </ul>
Maximal output power:	30 W / port PoE 802.3af/at
Maximal total power:	370 W
MAC addresses table:	16k
Operation modes:	<ul style="list-style-type: none"> <li>• Default : 100 m, 100 Mbps</li> <li>• Extend : 250 m, 10 Mbps</li> <li>• VLAN - 1 ... 24 ports are isolated from each other and separately work with the G1, G2 ports</li> </ul>
Main features:	<ul style="list-style-type: none"> <li>• High priority ports : 1 ... 8</li> <li>• Data Flow Control</li> <li>• Buffer optimization</li> <li>• Power supply PoE - wires : 4-5(+), 7-8(-)</li> <li>• Metal housing</li> <li>• Can be mounted in a Rack 19" cabinet</li> </ul>
Certificates:	CE, FCC
Housing:	Desktop, Metal
Power supply:	100 ... 240 V AC, 50 / 60 Hz
Operation temp:	0 °C ... 40 °C
Weight:	2.89 kg
Dimensions:	440 x 245 x 44 mm, RACK 19", 1U
Manufacturer / Brand:	UNIVIEW



# DATA SHEET

---

Guarantee:	2 years
------------	---------