

Code: COMO-PRO-CODE-A1-NT

## DIGITAL DOORPHONE **COMO-PRO-CODE-A1-NT** ACO

The COMO panels are dedicated to single and multi-family homes.

The combination of modern technology with brushed stainless steel creates timeless solutions for individual customers who appreciate design and functionality.



Compatibility:	ACO COMO PRO
Method of mounting:	Surface
proximity reader built-in:	Unique EM 125kHz
The number of subscribers served:	1
Inputs:	2 x screw connectors - External open button NO
Outputs:	<ul style="list-style-type: none"> <li>• 1 x RJ45 - Bus connector PRO digital system</li> <li>• 5 x screw connectors - Bus connector ACO COMO PRO               <ul style="list-style-type: none"> <li>- Audio</li> <li>- Power supply</li> <li>- Video input</li> </ul> </li> <li>• 2 x screw connectors               <ul style="list-style-type: none"> <li>- Connectors for connecting an electric door lock : 1.5 A (max)</li> <li>- Connectors for connecting the CDN-PK relay module</li> </ul> </li> </ul>
Line length:	1000 m (max)
Installation type:	PRO digital system : 3 wires or UTP cat. 5e, 6

Main features:	<ul style="list-style-type: none"> <li>- Acoustic and visual signalling of panel functions</li> <li>- Opening the door without answering the call</li> <li>- Possibility of connecting an additional acoustic or luminous device to indicate ringing</li> <li>- Support for 1020 individual opening codes</li> <li>- Support for up to 10240 keyfobs, including 10 administrative keyfobs</li> <li>- Acoustic information in the premises about the opening of the door</li> <li>- Adding and deleting proximity keyfobs with the "master" keyfob (separately for each premise) and with the "super master" keyfob (in all premises)</li> </ul>
Power supply:	15 V DC / 400 mA
Power consumption:	~ 2.5 W
Housing:	Stainless steel
"Index of Protection":	—
Operation temp:	-20 °C ... 50 °C
Weight:	0.595 kg
Dimensions:	177 x 71 x 42 mm
Manufacturer / Brand:	ACO
Guarantee:	2 years

