

Code: TC-C32SS SPEC:I3/A/E/Y/M/S/H/2.7-13.5MM/V4.0

IP CAMERA **TC-C32SS SPEC:I3/A/E/Y/M/S/H/2.7-13.5MM/V4.0** - 1080p 2.7 ... 13.5 mm - MOTOZOOM TIANDY

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

The used motozoom lens with 2.7 ... 13.5 mm focal length allows to remote view angle adjustment. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



Standard:	IP
Sensor:	1/2.8 " Progressive Scan CMOS
Resolution:	1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens:	2.7 ... 13.5 mm - Motozoom
View angle:	96 ° ... 31 °
Range of IR illumination:	30 m
Image compression method:	S+265 / H.265 / H.264
Main stream frame rate:	max. 25 fps - 2.1 Mpx
Network interface:	10/100 Base-T (RJ-45)
Alarm inputs / outputs:	1 / 1



DATA SHEET

Audio:	<ul style="list-style-type: none">• Microphone built-in• External microphone input• Audio output• Bi-directional audio streaming support• Audio transmission via network• Compliance with the AAC standard
WEB Server:	Built-in
Max. number of on-line users:	2
ONVIF:	✓
Memory card slot:	Micro SD card support up to 512GB
Mobile phones support:	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application EasyLive Plus• iOS (iPhone): Free application EasyLive Plus
Access from PC:	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Default IP address:	192.168.1.2
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports:	3000, 3001
PC client access ports:	3000, 3001
Port ONVIF:	80
Intelligent image analysis:	<ul style="list-style-type: none">• classification of people and vehicles• video tampering• crossing the line (tripwire)• intrusion• Audio detection• face detection
Main features:	<ul style="list-style-type: none">• WDR - 120 dB - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• F-DNR (Defog) - Reduction of image noise caused by precipitation• ROI - improve the quality of selected parts of image• BLC - Back Light Compensation• HLC - High Light Compensation (spot)• Possibility to change the resolution, quality and bit rate• ICR - Movable InfraRed filter• Day/Night mode - configurable• Motion Detection• Privacy zones• Mirror - Mirror image• Sharpness - sharper image outlines
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 660 mA
Power consumption:	≤ 8.5 W
Housing:	Dome - Metal
Color:	White
"Index of Protection":	IP66



DATA SHEET

Mechanical protection class:	—
Operation temp:	-35 °C ... 65 °C
Weight:	0.68 kg
Dimensions:	Ø 132 x 108 mm
Supported languages:	Polish, English, Albanian, Arabic, Spanish, Korean, Russian, French, Dutch, Hebrew, German, Portuguese, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand:	TIANDY
Guarantee:	3 years