

Code: BCS-L-DIP25FSR4-AI2

## IP VANDALPROOF CAMERA **BCS-L-DIP25FSR4-AI2** - 5 Mpx 2.8 mm BCS Line

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 5 MPx.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



Standard:	IP
Resolution:	2960 x 1668 - 5 Mpx , 2880 x 1620 - 4 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 4 Mpx , 2304 x 1296 - 3 Mpx , 2048 x 1536 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor:	1/2.7 " Progressive Scan CMOS
Lens:	2.8 mm
View angle:	<ul style="list-style-type: none"> <li>• 111 ° (manufacturer data)</li> <li>• 105 ° (our tests result)</li> </ul>
Range of IR illumination:	50 m
RS-485 interface:	—
Memory card slot:	Micro SD card support up to 512GB
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	1 / 1



# DATA SHEET

Audio:	<ul style="list-style-type: none"><li>• Microphone built-in</li><li>• Audio input</li><li>• Audio output</li><li>• Bi-directional audio streaming support</li><li>• Audio detection</li></ul>
Main stream frame rate:	25 fps @ 5 Mpx
Interface:	10/100 Base-T (RJ-45)
WEB Server:	Built-in
ONVIF:	✓
Intelligent image analysis:	<ul style="list-style-type: none"><li>• intrusion</li><li>• crossing the line (tripwire)</li><li>• classification of people and vehicles</li><li>• fast moving</li><li>• loitering</li><li>• crowd detection</li><li>• parking detection</li><li>• person/vehicle recognition for area intrusion</li><li>• abandoned/missing object</li><li>• face detection and tracking - recognition of facial attributes and expressions</li><li>• people counting</li><li>• heat map</li></ul>
Main features:	<ul style="list-style-type: none"><li>• WDR - 120 dB - Wide Dynamic Range</li><li>• 3D-DNR - Digital Noise Reduction</li><li>• ROI - improve the quality of selected parts of image</li><li>• BLC/HLC - Back Light / High Light Compensation</li><li>NAS - Network Attached Storage support</li><li>• SMD 3.0 - searching for an object classified as: human, motor vehicle</li></ul>
Mobile phones support:	Access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">BCS Manager</a></li><li>• iOS (iPhone): Free application <a href="#">BCS Manager</a></li></ul>
Access from PC:	Port no.: 37777 or access by a cloud (P2P) - PC: Free application <a href="#">BCS Manager</a>
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	192.168.1.108
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Power supply:	<ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC / 740 mA</li></ul>
Power consumption:	≤ 8,8 W
Housing:	Compact - Metal
Color:	White



# DATA SHEET

"Index of Protection":	IP67
Mechanical protection class:	IK10
Operation temp:	-40 °C ... 60 °C
Weight:	0.515 kg
Dimensions:	Ø 89 x 111 mm
Supported languages:	Polish, English
Manufacturer / Brand:	BCS Line
Guarantee:	<b>3 years</b>