

Code: TC-C35WS SPEC:I5/E/Y/2.8MM/V4.0

IP CAMERA **TC-C35WS SPEC:I5/E/Y/2.8MM/V4.0** - 5 Mpx 2.8 mm TIANDY

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

Attention! Enabling the ONVIF protocol in the camera disables P2P access.



Standard:	IP
Resolution:	2592 x 1944 - 5 Mpx , 2592 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor:	1/2.8 " Progressive Scan CMOS
Lens:	2.8 mm
View angle:	94 °
Range of IR illumination:	50 m
Memory card slot:	Micro SD card support up to 512GB
Image compression method:	S+265 / H.265 / H.264
Alarm inputs / outputs:	—
Audio:	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network



DATA SHEET

Main stream frame rate:	<ul style="list-style-type: none">• 20 fps @ 5 Mpx• 25 fps @ 4 Mpx
Interface:	10/100 Base-TX (RJ-45)
WEB Server:	Built-in
Max. number of on-line users:	2
ONVIF:	✓
Mobile phones support:	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application EasyLive Plus• iOS (iPhone): Free application EasyLive Plus
Access from PC:	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Default IP address:	DHCP or 192.168.1.2
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports:	3000, 3001
PC client access ports:	3000, 3001
Port ONVIF:	80
Intelligent image analysis:	<ul style="list-style-type: none">• crossing the line (tripwire)• intrusion
Main features:	<ul style="list-style-type: none">• WDR - 120 dB - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• F-DNR (Defog) - Reduction of image noise caused by precipitation• ROI - improve the quality of selected parts of image• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its• BLC/HLC - Back Light / High Light Compensation• ICR - Movable InfraRed filter• Day/night mode• Motion Detection
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 590 mA
Power consumption:	≤ 7 W
Housing:	Compact - Metal + Plastic
Color:	White
"Index of Protection":	IP67
Mechanical protection class:	—
Operation temp:	-40 °C ... 65 °C
Weight:	0.31 kg
Dimensions:	160 x 73 x 73 mm



DATA SHEET

Supported languages:	Polish, English, Albanian, Arabic, Spanish, Korean, French, Dutch, Hebrew, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand:	TIANDY
Guarantee:	3 years