

## DATA SHEET

Code: APTI-W30S2-TUYA

## PTZ OUTDOOR IP CAMERA **APTI-W30S2-TUYA** Tuya Smart Wi-Fi, - 3 Mpx 3.6 mm

The cameras cooperating with the user-friendly Tuya platform have been designed with special care to simplify the configuration process and enable the user to create a simple and effective monitoring system.

The free Tuya Smart application will send a notification to your phone when the sensors in the camera detect movement or sound, and you can control the device at any time, regardless of where you are - all you need is Internet access and a smartphone.

Tuya Smart application works perfectly with Google Assistant, Amazon Alexa and many others, which allows you to control connected devices using voice commands.

**Attention!** Devices cooperating with the Tuya platform do not have a WEB interface. Controlling the device and schedule settings is possible if the device has access to the Internet.



Standard:	IP
Resolution:	2304 x 1296 - 3 Mpx
Sensor:	Progressive Scan CMOS
Lens:	3.6 mm
View angle:	50 °
Range of IR illumination:	20 m
White light LED illuminator range:	20 m
Horizontal rotation range:	0 ° 350 ° Rotation of the head is limited by stops
Vertical rotation range:	0 ° 93 °
Audio:	Microphone built-in,     Speaker built-in,     Audio transmission via network,     Bi-directional audio streaming support
Main stream frame rate:	10 fps
Network interface:	• Wi-Fi - IEEE 802.11 b/g/n, • Ethernet - 10 / 100 Mbps (RJ-45)
ONVIF:	<b>→</b>





## DATA SHEET

WEB Server:	-
Mobile phones support:	Access by a cloud (P2P)  • The <u>Tuya Smart</u> free application on Android  • The <u>Tuya Smart</u> free application on iOS
Default IP address:	DHCP
Web browser access ports:	_
PC client access ports:	_
Mobile client access ports:	_
RTSP URL:	_
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Main features:	Wi-Fi module - IEEE 802.11 b/g/n, Range : 30 m (open area)     Cooperation of the Tuya Smart application with Google Assistant, Amazon Alexa     RESET button
Power supply:	12 V DC 2 A (power adapter not included)
Housing:	Mini Speed Dome, Plastic
Weight:	0.311 kg
Dimensions:	160 x 145 x 100 mm
Operation temp:	-10 °C 60 °C
Supported languages:	English
Guarantee:	2 years