

Code: CDNA-GR

ANALOG DOORPHONE **CDNA-GR** ACO



The CDNA doorphone panels are modern devices with digital dialing of the premises and code-based door opening.

| | |
|-----------------------------------|--|
| Compatibility: | ACO CDN |
| Method of mounting: | Can be flush or surface mounted depending on the frame selected |
| proximity reader built-in: | — |
| The number of subscribers served: | 64 premises |
| Display: | LED |
| Backlight: | ✓ |
| Inputs: | 1 x NO - Bell push-button |
| Outputs: | Connection of a traditional, reversible electric door strike or CDN-PK relay module |
| Line length: | 300 m (max) |
| Installation type: | Analog doorphone installation, 4, 5, 6-wire |
| Main features: | <ul style="list-style-type: none"> • Acoustic and visual signalling of panel functions • Support for multiple expansion modules to increase system functionality • Ability to connect multiple active receivers under the same number • Corridor opening function • Control of external devices, e.g. entrance gate, barrier, lighting, roller shutters |



DATA SHEET

| | |
|-----------------------|---|
| Power supply: | 15 V DC / 140 mA or 12 V AC \pm 0.5 V |
| Power consumption: | ~ 0.9 W |
| Housing: | Aluminum - powder painted |
| Weight: | 0.335 kg |
| Dimensions: | 205 x 88 x 30 mm |
| Manufacturer / Brand: | ACO |
| Guarantee: | 2 years |