

Code: COVER-WINTER-3K

UPS **COVER-WINTER-3K** 3000 VA COVER

The COVER-WINTER-3K UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The device is mounted to RACK 19" cabinet.

The line-interactive power supplies analyse the voltage, frequency and phase shift angle on a current basis, and filter the voltage transmitted to the connected devices. When a mains failure is detected, the UPS immediately switches to autonomous operation mode and continues to power the equipment using the energy accumulated in internal batteries.



Power adapter type:	Line-interactive
Nominal power:	2700 W
Apparent Power:	3000 VA
Input voltage:	162 V ... 290 V AC
Input frequency:	50 / 60 Hz
Output voltage:	208 V / 220 V / 230 V / 240 V AC (Pure Sine Wave)
Power factor:	0.9
Output frequency:	50 / 60 Hz (auto detection) \pm 1 Hz
Transfer time:	max. 6 ms
Voltage adjustment:	—
Frequency adjustment:	—
Charging time (recover to 90% capacity):	8 hours
Battery:	6 pcs

Estimated battery operation time:	<ul style="list-style-type: none"> • 12 minutes @ 1350 W, • 7 minutes @ 2025 W, • 4 minutes @ 2700 W
Number of outputs:	8 pcs IEC-320 C13 + 1 pcs IEC-320 C19
Management software:	ViewPower
Protections:	<ul style="list-style-type: none"> • Short-circuit • Overload • Overcharge protection • discharge protection • Output voltage filtering • EPO (Emergency power off) switch
Operation state indication:	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, • Sound signaling
Main features:	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic bypass • The device has a rotating display • COLD START function for manual switch to the battery power supply • Battery charge and maintenance control • Port RS-232 - Access from PC • Remote management - ViewPower application (included) • Battery replacement during operation (Hot-swap) • Network card slot • Can be mounted in a Rack 19" cabinet
Application:	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Rack/Tower 2-in-1 Design
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ~ 95 % (non-condensing)
Weight:	29.2 kg
Dimensions:	438 x 630 x 88 mm ; RACK 19", 2U
Manufacturer / Brand:	COVER
Guarantee:	2 years