

Code: DS-E04NI-Q1/4P(SSD1T)

## NVR **DS-E04NI-Q1/4P(SSD1T)** 4 CHANNELS, 4 PoE Hikvision

HIKVISION mini IP DVR with built-in SSD drive. The H.265+ video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.

**Attention!** The recorder has a built-in SSD drive with a capacity of 1TB.



Standard:	IP
Supported resolutions:	max. 4 Mpx
Video outputs:	1 pcs HDMI
Audio support:	4 Channels - Audio from cameras
Audio inputs:	—
Audio outputs:	—
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Bitrate:	max. 40 Mbps
Supported hard drives:	1 x 1 TB SATA, The recorder has a built-in SSD drive with a capacity of 1TB
Recording modes:	Manual, Motion Detection, Schedule
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Records playback from max. 4 channels in the same time @ 1080p Smart Search function Smart Playback function
Interface:	1 x RJ-45 10/100 Base-TX
Network functions:	Live image view, Playback the records, Backup the records - iVMS-4200 application The device has the ability to work with the <a href="#">Hik-Connect</a> application for mobile devices
ONVIF:	✓
Default IP address:	192.168.1.64
Default admin user / password:	admin / - The administrator password should be set at the first start



# DATA SHEET

Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">Hik-Connect</a></li><li>• iOS: Free application <a href="#">Hik-Connect</a></li></ul>
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
RTSP URL:	<ul style="list-style-type: none"><li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/</li><li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/</li></ul>
USB:	2 pcs USB 2.0
Serial port:	—
Alarm inputs / outputs:	—
PTZ control:	IP Speed Dome Cameras
Motion Detection:	✓
Intelligent image analysis:	✓
Mouse support:	✓
IR remote controller in the set:	—
Switch PoE:	4-port PoE Switch built-in, 25.5 W / Channel - PoE (802.3af/at)
Maximum total switch load:	36 W
Power supply:	48 V DC / 1 A (power adapter included)
Power consumption:	≤ 10 W
Operation temp:	-10 °C ... 45 °C
Weight:	0.4 kg
Dimensions:	160 x 112 x 27 mm
Supported languages:	Polish, English
Manufacturer / Brand:	Hikvision
SAP Code:	303618927
Guarantee:	<b>3 years</b>