

Code: NVR2108HS-8P-4KS3

## NVR **NVR2108HS-8P-4KS3** 8 CHANNELS, 8 PoE DAHUA



|                                     |   |
|-------------------------------------|---|
| Standard:                           | IP  |
| Supported resolutions:              | max. 12 Mpx - 4000 x 3000 px  |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA  |
| Audio support:                      | 8 Channels - Audio from cameras   |
| Audio inputs:                       | 1 pcs CINCH   |
| Audio outputs:                      | 1 pcs CINCH   |
| Image compression method:           | H.265+, H.265, H.264+, H.264  |
| Supported hard drives:              | 1 x 20 TB SATA  |
| Recording modes:                    | Manual, Motion Detection, Schedule  |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)  |
| Searching and playback the records: | <ul style="list-style-type: none"> <li>Records searching: by time and events type. Records playback: forward, backward, fast, slow</li> <li>Advanced searching (to the one second accuracy)</li> <li>Synchronous playback of all channels</li> <li>Smart Playback function</li> </ul>                         |
| Bitrate:                            | max. 144 Mbps   |
| Network functions:                  | Full support via network, Remote records copying, Web-Server built-in<br>max. 128 on-line users   |
| Mobile phones support:              | Port no.: 37777 or access by a cloud (P2P)<br><ul style="list-style-type: none"> <li>Android: Free application <a href="#">DMSS</a></li> <li>iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul> See how to configure the P2P function in Dahua recorders and how to enable the mobile application |
| Default admin user / password:      | admin / admin   |



# DATA SHEET

|                                  |   |
|----------------------------------|---|
| Default IP address:              | 192.168.1.108   |
| Web browser access ports:        | 80, 37777   |
| PC client access ports:          | 37777   |
| Switch PoE:                      | 8-port PoE Switch built-in, 25.5 W / Channel, PoE (802.3af/at)  |
| Maximum total switch load:       | 72 W  |
| Mobile client access ports:      | 37777   |
| RTSP URL:                        | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream |
| Alarm inputs / outputs:          | —   |
| PTZ control:                     | IP Speed Dome Cameras   |
| Motion Detection:                | ✓   |
| USB:                             | 2 pcs USB 2.0   |
| Mouse support:                   | ✓   |
| IR remote controller in the set: | —   |
| Power supply:                    | 53 V DC / 1.81 A (power adapter included)   |
| Weight:                          | 0.89 kg   |
| Dimensions:                      | 260 x 225 x 48 mm   |
| Supported languages:             | English, Bulgarian, Czech, Finnish, Greek, Polish, Romanian, Serbian, Slovenian, Hungarian  |
| Country of origin:               | China   |
| Manufacturer / Brand:            | DAHUA   |
| Guarantee:                       | <b>3 years</b>  |

