

Code: T4A-PV

IP CAMERA **T4A-PV** Wi-Fi, Smart Dual Light Active Deterrence - 3.7 Mpx 2.8 mm DAHUA

IP Wi-Fi camera with efficient H.265 image compression algorithm for clear and smooth video streaming at max. resolution of 4 Mpx.

The device is equipped with Smart Dual Light technology, thanks to which the user has a choice of white light mode and IR (infrared) mode. When Smart Dual Light is active, the white light will turn on automatically only when an object is detected in the monitored area, which effectively improves the image quality.

In addition, the camera has the function of active deterrence of intruders using a motion-activated white light LED spotlight and siren sound.



| | |
|------------------------------------|--|
| Standard: | IP |
| Resolution: | 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p |
| Sensor: | 1/3 " Progressive Scan CMOS |
| Lens: | 2.8 mm |
| View angle: | 98 ° |
| Range of IR illumination: | 30 m |
| White light LED illuminator range: | 30 m |
| S/N ratio: | > 56 dB |
| Memory card slot: | Micro SD memory cards up to 256GB support (possible local recording) |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 |
| Alarm inputs / outputs: | — |



DATA SHEET

| | |
|--------------------------------|---|
| Audio: | <ul style="list-style-type: none">• Microphone built-in,• Speaker built-in,• Bi-directional audio streaming support• Audio output• Audio detection |
| Main stream frame rate: | 25 fps @ 4 Mpx |
| Interface: | <ul style="list-style-type: none">• Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz,• 10/100 Base-T (RJ-45) |
| WEB Server: | Built-in |
| Max. number of on-line users: | 20 |
| ONVIF: | ✓ |
| Mobile phones support: | Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application DMSS• iOS (iPhone): Free application DMSS |
| Default IP address: | 192.168.1.108 |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Web browser access ports: | 80, 37777 |
| PC client access ports: | 37777 |
| Mobile client access ports: | 37777 |
| Port ONVIF: | 80 |
| RTSP URL: | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream |
| Main features: | <ul style="list-style-type: none">• Active deterrence function• D-WDR - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• ROI - improve the quality of selected parts of image• BLC/HLC - Back Light / High Light Compensation• Possibility to change the resolution, quality and bit rate• Mirror - Mirror image• Image rotation and mirror• Motion Detection - max. 4 configurable zones - Human detection• Privacy zones - max. 4 |
| Power supply: | 12 V DC / 600 mA (power adapter included) |
| Power consumption: | ≤ 7.1 W |
| Housing: | Dome - Plastic |
| Color: | White |
| "Index of Protection": | IP67 |
| Mechanical protection class: | — |
| Operation temp: | -40 °C ... 60 °C |
| Weight: | 0.32 kg |
| Dimensions: | Ø 110 x 102 mm |



DATA SHEET

| | |
|-----------------------|-----------------|
| Supported languages: | Polish, English |
| Manufacturer / Brand: | DAHUA |
| Guarantee: | 3 years |

