

Code: DS-KD7003EY-IME2/ALUMINUM

VIDEO DOORPHONE **DS-KD7003EY-IME2/ALUMINUM** Hikvision

The DS-KD7003EY-IME2/ALUMINUM module is the main unit of the video doorphone modular system of Hikvision brand.

The product is compatible with Hikvision 2-wire video intercoms from the EY series.



Compatibility:	HIKVISION 2-wire - EY series
Doorbell button:	2 pcs
Sensor:	2 Mpx
Camera view angle:	133 °
Image compression method:	H.264
IR illuminator:	✓
Alarm inputs:	2 pcs
Relay outputs:	1 x NO/NC

Main features:	<ul style="list-style-type: none"> • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Noise suppression and echo cancellation, • Tamper detection - removing from mounting surface, • The panel is addressed using rotary switches, • Possibility to mount masking plate, 1, or 2 bell buttons as required, • Lock control : 1 x Pulse output 20 V / 4 A + 1 x Relay output NO/NC 30 V DC, • Installation of DS-KD-xx series modules takes place in dedicated DS-KD-ACF series housings (flush-mounted housings) and DS-KD-ACW series housings (surface-mounted housings)
Power supply:	<ul style="list-style-type: none"> • 48 V DC - HIKVISION 2-wire, • 12 V DC
Power consumption:	< 6 W
Operation temp:	-40 °C ... 60 °C
Housing:	Metal
Color:	Black
"Index of Protection":	IP65
Mechanical protection class:	IK10
Weight:	0.28 kg
Dimensions:	100 x 98 x 35 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305304875
Guarantee:	3 years