

Code: TC-C382V SPEC:W/E/Y/S/H/2.8MM

## IP CAMERA **TC-C382V SPEC:W/E/Y/S/H/2.8MM** PANORAMIC Full-Color - 8 Mpx 2 X 2.8 mm TIANDY

The IP camera is equipped with 2 high quality image sensors and 2 lenses with 2.8 mm focal length. Thanks to its unique design, the camera has a 180° viewing angle.

PoE powering possibility, compatible with the 802.3at standard makes the device more universal and easier to install. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).



|                                    |                                                                                                                                                                                                                                                                                             |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                          | IP                                                                                                                                                                                                                                                                                          |
| Resolution:                        | 4640 x 1728 - 8 Mpx                                                                                                                                                                                                                                                                         |
| Sensor:                            | 2 x 1/2.7 " Progressive Scan CMOS                                                                                                                                                                                                                                                           |
| Lens:                              | 2 x 2.8 mm                                                                                                                                                                                                                                                                                  |
| View angle:                        | <ul style="list-style-type: none"> <li>• 180 ° (manufacturer data)</li> <li>• 180 ° (our tests result)</li> </ul>                                                                                                                                                                           |
| Range of IR illumination:          | —                                                                                                                                                                                                                                                                                           |
| White light LED illuminator range: | 15 m                                                                                                                                                                                                                                                                                        |
| Min. illumination:                 | 0.0001 Lux / F1.0 (color)                                                                                                                                                                                                                                                                   |
| Memory card slot:                  | Micro SD card support up to 512GB                                                                                                                                                                                                                                                           |
| RS-485 interface:                  | ✓                                                                                                                                                                                                                                                                                           |
| Image compression method:          | S+265 / H.265 / H.264                                                                                                                                                                                                                                                                       |
| Alarm inputs / outputs:            | 1 / 1                                                                                                                                                                                                                                                                                       |
| Audio:                             | <ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Speaker built-in</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> </ul> |
| Main stream frame rate:            | 25 fps @ 8 Mpx                                                                                                                                                                                                                                                                              |
| Interface:                         | 10/100 Base-TX (RJ-45)                                                                                                                                                                                                                                                                      |
| WEB Server:                        | Built-in                                                                                                                                                                                                                                                                                    |
| Max. number of on-line users:      | 7                                                                                                                                                                                                                                                                                           |
| ONVIF:                             | ✓                                                                                                                                                                                                                                                                                           |



# DATA SHEET

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mobile phones support:         | Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">EasyLive Plus</a></li><li>• iOS (iPhone): Free application <a href="#">EasyLive Plus</a></li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Access from PC:                | Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Default IP address:            | DHCP or 192.168.1.2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Web browser access ports:      | 80, 443, 3000, 3001, 3002, 23002                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Mobile client access ports:    | 3000, 3001                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| PC client access ports:        | 3000, 3001                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Port ONVIF:                    | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Intelligent image analysis:    | <ul style="list-style-type: none"><li>• crossing the line (tripwire)</li><li>• intrusion</li><li>• classification of people and vehicles</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Main features:                 | <ul style="list-style-type: none"><li>• WDR - 120 dB - Wide Dynamic Range</li><li>• 3D-DNR - Digital Noise Reduction</li><li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li><li>• BLC/HLC - Back Light / High Light Compensation</li><li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li><li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li><li>• ROI - improve the quality of selected parts of image</li><li>• Day/night mode</li><li>• Possibility to change the resolution, quality and bit rate</li></ul> |
| Power supply:                  | <ul style="list-style-type: none"><li>• PoE (802.3at),</li><li>• 12 V DC / 920 mA</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Power consumption:             | <ul style="list-style-type: none"><li>• ≤ 12 W @ PoE</li><li>• ≤ 11 W @ 12 V DC</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Housing:                       | Compact - Metal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Color:                         | White                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| "Index of Protection":         | IP67                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Mechanical protection class:   | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Operation temp:                | -35 °C ... 65 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Weight:                        | 0.8 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Dimensions:                    | 294 x 116 x 72 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Supported languages:           | Polish, English, Albanian, Arabic, French, Hebrew, Spanish, Dutch, Korean, German, Portuguese, Thai, Ukrainian, Vietnamese, Italian                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Manufacturer / Brand:          | TIANDY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Guarantee:                     | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |