

Code: KMC-20-11

MODULAR CONTACTOR **KMC-20-11** 20 A 230 V AC IDEAL

The KMC-20-11 contactor has 1 NO contact and 1 NC contact. Both control and power supply voltage uses alternating current. The device has no manipulator for manual operation.

The KMC-20-11 device is designed to mount on DIN TH-35 rail.



Device type:	Contactor - NO/NC, One-phase
Nominal load current:	<ul style="list-style-type: none"> • 20 A @ AC7A / AC1, • 7 A @ AC7B
Rated load voltage:	230 V AC
Control voltage:	230 V AC
Nominal power:	<ul style="list-style-type: none"> • 4000 W @ 230 V AC7A • 1200 W @ 230 V AC7B
Number of NO/NC contacts:	1 / 1
Category of use:	AC1, AC7A, AC7B
Connectors type:	screw terminals
Main features:	<ul style="list-style-type: none"> • Operation temp : -25 °C ... 40 °C • Supported norms : PN-EN 60947-4-1, PN/EN 61095
Housing:	Plastic, DIN, TH-35 rail mounting
"Index of Protection":	IP20
Width in 17.5 mm modules:	1



DATA SHEET

Weight:	0.13 kg
Dimensions:	67 x 82 x 17.5 mm
Manufacturer / Brand:	IDEAL
Guarantee:	5 years