

Code: F2C-PV

IP CAMERA **F2C-PV** Wi-Fi, Smart Dual Light Active Deterrence - 1080p 2.8 mm DAHUA

IP Wi-Fi camera with efficient H.265 image compression algorithm for clear and smooth video streaming at max. resolution of 1080p.

The device is equipped with Smart Dual Light technology, thanks to which the user has a choice of white light mode and IR (infrared) mode. When Smart Dual Light is active, the white light will turn on automatically only when an object is detected in the monitored area, which effectively improves the image quality.

In addition, the camera has the function of active deterrence of intruders using a motion-activated white light LED spotlight and siren sound.



Standard:	IP
Resolution:	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Sensor:	1/3 " Progressive Scan CMOS
Lens:	2.8 mm
View angle:	98 °
Range of IR illumination:	30 m
White light LED illuminator range:	30 m
Memory card slot:	Micro SD card support up to 256GB
Image compression method:	H.265 / H.264 H.264B / H.264H
Alarm inputs / outputs:	—
Audio:	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support



DATA SHEET

Main stream frame rate:	25 fps @ 1080p
Interface:	<ul style="list-style-type: none">• Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz,• 10/100 Base-T (RJ-45)
WEB Server:	Built-in
ONVIF:	✓
Intelligent image analysis:	Human detection
Main features:	<ul style="list-style-type: none">• Active deterrence function• Smart Dual Light• Built-in hybrid illuminator (LED - IR/white)• Day/night mode• ICR - Movable InfraRed filter• D-WDR - Wide Dynamic Range• Possibility to change the resolution, quality and bit rate• Image rotation and mirror• Motion Detection
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application DMSS• iOS (iPhone): Free application DMSS
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
Port ONVIF:	80
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Power supply:	12 V DC / 1 A (power adapter included)
Power consumption:	≤ 6.5 W @ 12 V DC
Housing:	Compact - Plastic
Color:	White + Black
"Index of Protection":	IP67
Mechanical protection class:	—
Operation temp:	-40 °C ... 60 °C
Weight:	0.26 kg
Dimensions:	131 x 78 x 97 mm
Supported languages:	Polish, English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years