

Code: ST-601/ES

## VIDEO TESTER **ST-601/ES**

The LCD 2.5" color monitor built-in, new keyboard - the numeric keys are very useful and make the device is irreplaceable for CCTV installations.



Video standard:	PAL, NTSC
Display:	2.5 " TFT LCD 320x240
Video input:	1 pcs BNC
Video output:	1 pcs BNC
Video signal generator:	It is possible to generate the red, white, black, blue or green screen image
Serial ports:	RS-232, RS422 simplex, RS-485
Protocols:	Pelco-P, Pelco-D, SAMSUNG, YAAN, Imtech, vcl, Fastrax, everfocus, lgm, kdt, 304, kdt 405, kdt kb3, mlp2, mlp1, dynacolor, ad, videotrec, vicon, alec, csr600, csr600, a01, b01
Baud rates:	2400, 4800, 9600, 19200 bps
LAN (twisted-pair) or telephone cables testing:	Cable connection state is display on the screen (short circuit, disconnection, configuration - normal and cross connection)
Operation:	OSD menu full in Spanish
Battery power supply:	9 V DC (power adapter included) / 2x 3.7V / 1400mAh battery (included)
Estimated battery operation time:	5 hours (5 hours recharging time)
Operation temp:	-30 °C ... 70 °C
Permissible relative humidity:	-30 % ... 70 %



# DATA SHEET

Main features:	<ul style="list-style-type: none"><li>• Video signal test</li><li>• Motor units and PTZ (Speed Dome) cameras control</li><li>• LAN (twisted-pair) cables testing</li><li>• Video signal generating</li><li>• RS-485, RS-422, RS-232 lines testing</li></ul>
Weight:	0.29 kg
Dimensions:	170 x 99 x 48 mm
Guarantee:	2 years