

Code: VI-1500/LCD

## UPS **VI-1500/LCD** 1500 VA

The VI-1500/LCD UPS is a professional device used to maintain the operation of the components connected to it. Additionally protects the connected equipment against overvoltages.



Nominal power:	900 W
Apparent Power:	1500 VA
Input voltage:	162 ... 290 V AC
Output voltage:	230 V AC (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Charging time (recover to 90% capacity):	4 ... 6 hours
Estimated battery operation time:	18 minutes
Battery:	2 x 12V/9Ah
Number of outputs:	2 pcs
Number of inputs:	2 pcs
Transfer time:	2 ... 6 ms (max. 10 ms)
Management software:	ViewPower (Polish version - Windows 98/2000/XP/Vista/7/8, MAC, Linux, FreeBSD, Solaris)
Additional protection:	RJ11, RJ45
Protections:	<ul style="list-style-type: none"> <li>• Overcharge</li> <li>• Discharge</li> <li>• Short-circuit</li> </ul>



# DATA SHEET

Main features:	<ul style="list-style-type: none"><li>• Auto restart while AC is recovering</li><li>• Short-time charging</li><li>• Excellent microprocessor control guarantees high reliability</li><li>• Built-in AVR voltage stabilization system</li><li>• Battery charging at power-off mode</li><li>• "Cold Start" function</li><li>• USB interface</li><li>• Energy Saving function (possibility to deactivate from software)</li></ul>
Application:	to Home & Small Office applications
Operation state indication:	LCD display: operation mode, battery charging level, in/out voltage level
Housing type:	Tower
Dimensions:	397 x 147 x 205 mm
Weight:	10.52 kg
Guarantee:	2 years