

Code: VI-2000/LCD

UPS **VI-2000/LCD** 2000 VA

The VI-2000/LCD UPS is a professional device used to maintain the operation of the components connected to it. Additionally protects the connected equipment against overvoltages.



Nominal power:	1200 W
Apparent Power:	2000 VA
Input voltage:	162 ... 290 V AC
Output voltage:	230 V AC (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Charging time (recover to 90% capacity):	4 ... 6 hours
Estimated battery operation time:	20 minutes
Battery:	2 x 12V/9Ah
Number of outputs:	2 pcs
Number of inputs:	2 pcs
Transfer time:	2 ... 6 ms (max. 10 ms)
Management software:	ViewPower (Polish version - Windows 98/2000/XP/Vista/7/8, MAC, Linux, FreeBSD, Solaris)
Additional protection:	RJ11, RJ45
Protections:	• Overcharge • Discharge • Short-circuit

Main features:	• Auto restart while AC is recovering • Short-time charging • Excellent microprocessor control guarantees high reliability • Built-in AVR voltage stabilization system • Battery charging at power-off mode • "Cold Start" function • USB interface • Energy Saving function (possibility to deactivate from software)
Application:	to Home & Small Office applications
Operation state indication:	LCD display: operation mode, battery charging level, in/out voltage level
Housing type:	Tower
Dimensions:	397 x 147 x 205 mm
Weight:	11.92 kg
Guarantee:	2 years