

Code: 3B2-98RWM

PAL VANDALPROOF CAMERA **3B2-98RWM** 3.5 ... 8 mm

Vandal-proof camera with metal housing integrated with bracket. After remove the dome cover of the camera we can set the position of the camera module (it is adjusted on any axis), the field of view of the camera changing the zoom parameter of the vari-focal lens and change the image options using OSD menu. It is equipped with IR illuminator, which is turned on by twilight sensor when illumination conditions are low.

It has been equipped with extended OSD menu with many useful functions. The DNR (Digital Noise Reduction) function produces clear image, even at poor light conditions and high image gain parameters we will not see any image noise on the screen. WDR (SSDR) - Wide Dynamic Range function enables the correct exposure (not overexposed - not underexposed) of the image at extreme different illumination of the monitoring object.

Camera connectors (BNC and power) can be hidden inside the camera housing, what protects them against damage. Additionally, camera dome cover is protected against falling by metal cable.

Camera is according to IP55 Index of Protection norm.



Standard:	PAL
Sensor:	1/3 " Sony CCD
Resolution:	700 TVL
Lens:	3.5 ... 8 mm
View angle:	69 ° ... 33 °
Range of IR illumination:	20 m
S/N ratio:	> 50 dB
Video output:	1 Vpp / 75 Ω
Power supply:	12 V DC / 270 mA
Main features:	<ul style="list-style-type: none"> • WDR - Wide Dynamic Range • NR - Noise Reduction • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • Motion Detection - max. 4 zones • Privacy zones - max. 8 • Mirror - Horizontal mirror image • Sharpness - sharper image outlines
Vandal-proof:	✓
Permissible relative humidity:	max. 95 %
"Index of Protection":	IP55
Housing:	Dome - Metal
Color:	White
Operation temp:	-10 °C ... 50 °C
Weight:	1.1 kg



DATA SHEET

Dimensions:	183 x 132 x 146 mm
Supported languages:	English, Chinese, French, Spanish, German, Portuguese, Russian
Guarantee:	2 years

