

Code: GEMINI-510B

IP CAMERA **GEMINI-510B** - 720p

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at max. resolution of 720p (1.3 MPix). Very easy operation by Internet Explorer browser allows the users to convenient and remote support, and also remote management of the camera. Included camera software enables management and integrated monitoring of many network cameras. Its using allows to create large surveillance system.

ATTENTION! Camera software has implemented the option of sending the records and events messages via e-mails or FTP. Unfortunately in this camera model the option is inactive.



Sensor:	1/3 " Panasonic CMOS
Matrix size:	1.3 Mpx
Resolution:	1280x720 - 720p 704x576 - D1 352x288 - CIF
Lens:	—
Min. illumination:	0.1 Lux / F1.2 (AGC off)
S/N ratio:	> 50 dB
Auto Iris socket:	DC
RS-485 interface:	✓
Protocols:	Pelco-D, Pelco-P and others
Memory card slot:	Micro SD memory cards up to 32GB support (possible local recording)
Memory storage at Micro SD card recording:	~ 3.3 GB/h (internal file system - possibility to playback from camera only)
Compression:	H.264
Alarm inputs / outputs:	1 / 1 (detection zone setting)
Audio:	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support
Bitrate:	1792 ... 8192 kbps
Main stream frame rate:	max. 25 fps - 720p
Network interface:	10/100 Base-T (RJ-45)



Network protocols:	RTSP, NTP, UPNP
WEB Server:	Built-in
Max. number of on-line users:	10
ONVIF:	2.0
Mobile phones support:	Android, Blackberry, Windows mobile
Main features:	<ul style="list-style-type: none">• Possibility to change the resolution, quality and bit rate• Time mark and image description• Image rotation and mirror• Configurable: brightness, contrast, saturation• Privacy zones• DNR - Digital Noise Reduction• WDR - Wide Dynamic Range• Sharpness - sharper image outlines• Day/Night mode - configurable• Possibility to add different privileges to the users
Power supply:	12 V DC / 0.42 A
Housing:	Metal
Color:	White
Operation temp:	0 °C ... 60 °C
Weight:	0.51 kg
Dimensions:	148 x 81 x 72 mm
Guarantee:	2 years