

DATA SHEET

Code: JA-83M

WIRELESS MAGNETIC CONTACT JA-83M JABLOTRON

The JA-83M wireless detector (magnetic contact) is used to protection the windows and doors. Its small dimensions of (75 x 31 x 23 mm) ensure good aesthetics and enable easy mounting to the window or door frame. It is equipped with one side contact, depending on the needs it can be installed vertically or horizontally. Detector can work in two modes, you can switch between them. In the first mode an open signal is sent only, in the second mode both open and close signals are sent.

The device communicates with alarm control panel wirelessly via OASiS protocol.



| Detection: | Opening the door or window |
|---|--|
| Alarm signaling: | Signal to control panel |
| Frequency range: | 868 MHz OASiS protocol |
| Radio communication range (at open area): | max. 300 m |
| Battery: | CR123A 3 V (not included) |
| Backup time: | ~ 3 years (20 activations a day) |
| Environment class: | Grade 2 |
| Operation temp: | -10 °C 40 °C |
| Color: | White |
| Weight: | 0.04 kg |
| Dimensions: | • Transmitter: 75 x 31 x 23 mm • Magnet A: 56 x 16 x 15 mm • Magnet B: 10 x 4 mm |
| Manufacturer / Brand: | JABLOTRON |
| Guarantee: | 2 years |