

DATA SHEET

Code: VMT-555M

MONITOR VGA, 2XVIDEO IN, 2XVIDEO OUT, S-VIDEO, HDMI, AUDIO, REMOTE CONTROLLER **VMT-555M** 54.6 " VILUX

CCTV monitor with solid metal housing.

It has two types of mounting. As standalone with included stands and VESA 600x400 and VESA 800x400 mounting. This model is equipped with all kinds of inputs, what allows to display an image from any kind of signals using in CCTV systems.

Monitor is designed to the display of advertising spots from computer in public places such as waiting rooms, etc. Very interesting solution is placing the speakers of the back side of housing. It does not bother listening to the AUDIO from the recorder at the same time does not reduce the area of the monitor front panel.

The device is designed to continuous work in closed spaces.



Screen size:	54.6 "
Native resolution:	1920 х 1080 рх
Aspect ratios:	16:9
Matrix type:	TFT-LCD color matrix
Matrix backlight:	CCFL
Supported standards:	PAL/NTSC
Contrast:	4000 : 1
Brightness:	500 cd/m ²
Viewable angles:	178 ° horizontal 178 ° vertical
Response time:	9 ms
Speakers built-in:	2 x 10 W
Signal connectors:	 Composite Video (BNC) sockets: 2x in, 2x out 1x VGA 1x HDMI 1x S-VIDEO Audio input: (Jack - works with VGA input) 2x audio input: 2x Cinch L/R - works with BNC input
Housing type:	Metal



DATA SHEET

Monitor mounting standard:	• VESA 600x400 • VESA 800x400
Power supply:	230 V AC
Power consumption:	max. 220 W (operation)
Monitor control:	OSD - by IR remote controller or monitor control keys
Main features:	 3D Comb Filter 3D Noise Reduction PIP and POP functions - picture in picture and two pictures side by side Auto Picture Adjustment
Operation temp:	-20 °C 60 °C
Weight:	38.2 kg
Dimensions:	• 1255 x 745 x 64 mm (without stand) • 1255 x 790 x 200 mm (with stand)
Supported languages:	English, Chinese, French, Spanish, German, Portuguese, Russian, Italian
Manufacturer / Brand:	VILUX
Guarantee:	2 years