

Code: APTI-14V3-2812B

IP VANDALPROOF CAMERA **APTI-14V3-2812B** - 960p 2.8 ... 12 mm

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 1280x960. Very easy operation by Internet Explorer browser allows the users to convenient and remote support, and also remote management of the camera. Included camera software enables management and integrated monitoring of many network cameras. Its using allows to create large surveillance system.
ICR - The movable IR filter allows to perfect colors reproduction in daylight and wide gray-scale with high sharpness of the image at night mode.



Standard:	TCP/IP
Digital Image Processor:	Hisilicon 3518C
Sensor:	1/3 " Sony CMOS IMX225
Matrix size:	1.4 Mpx
Resolution:	1280 x 960 - 960p 1280 x 720 - 720p
Lens:	2.8 ... 12 mm, 2.0 Mpx
View angle:	81 ° ... 23 ° (manufacturer data) 83 ° ... 33 ° (our tests result)
S/N ratio:	> 50 dB
Range of IR illumination:	30 m
Memory card slot:	—
Image compression method:	H.264
Bitrate:	64 ... 12000 kbps
Main stream frame rate:	max. 25 fps - 1.3 Mpx
Network interface:	10/100 Base-T (RJ-45)
Alarm inputs / outputs:	—
Network protocols:	RTSP, FTP, PPPOE, DHCP, DDNS, NTP, UPnP, TCP
Audio:	—



DATA SHEET

WEB Server:	Built-in
Max. number of on-line users:	10
ONVIF:	2.0
RS-485 interface:	—
Mobile phones support:	—
Default admin user / password:	admin / admin
Default IP address:	192.168.1.168
Web browser access ports:	80
PC client access ports:	80
Mobile client access ports:	80
Port ONVIF:	80
RTSP URL:	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Main features:	• ICR - Movable InfraRed filter • Possibility to change the resolution, quality and bit rate • Motion Detection • Privacy zones • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Mirror - Mirror image • Day/Night mode - configurable
Power supply:	12 V DC / 580 mA
Housing:	Dome - Metal
Vandal-proof:	✓
Color:	Black
"Index of Protection":	IP66
Operation temp:	-20 °C ... 55 °C
Weight:	0.63 kg
Dimensions:	Ø 120 x 95 mm
Supported languages:	English
Manufacturer / Brand:	APTI
Guarantee:	2 years