

Code: RAPID-Y41

HD-CVI, PAL DVR **RAPID-Y41** 4 CHANNELS

Recorder working in HD-CVI - High Definition Composite Video Interface standard.

The HD-CVI interface allows to transmission of analog, composite video signal via coaxial cable. Via single coaxial cable can be transmitted three signals: video, audio and control. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.



Standard:	HD-CVI, PAL
Maximal total frame rate:	48 fps @ 1920 x 1080 px, 100 fps @ 1280 x 720 px, 100 fps @ 960 x 576 px, 100 fps @ 704 x 576 px, 100 fps @ 704 x 288 px, 100 fps @ 352 x 576 px, 100 fps @ 352 x 288 px
Recording speed adjustment:	1 ... 12 fps @ 1920 x 1080 1 ... 25 fps @ 1280 x 720 1 ... 25 fps @ 960 x 576 1 ... 25 fps @ 704 x 576 1 ... 25 fps @ 704 x 288 1 ... 25 fps @ 352 x 576 1 ... 25 fps @ 352 x 288 for each channel
Video inputs:	4 pcs BNC, HD-CVI, PAL
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	6
Image records resolutions:	1920 x 1080 1280 x 720 960 x 576 704 x 576 704 x 288 352 x 576 352 x 288
Recording modes:	Manual, Sensor, Motion detection, Schedule
Supported hard drives:	1 x 4 TB SATA



DATA SHEET

External storage devices backup:	Download records from backup to USB drive
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Mobile phones support:	Iphone and Android applications
Alarm inputs / outputs:	—
PTZ control:	HD-CVI or RS-485 PELCO-D/P
Motion Detection:	Split the screen into zones 22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 3 A (power adapter included)
Weight:	1.26 kg
Dimensions:	335 x 269 x 51 mm
Supported languages:	English, Arabic, Bulgarian, Chinese, Czech, French, Spanish, German, Polish, Russian, Romanian, Slovenian, Thai, Turkish, Hungarian, Italian
Country of origin:	China
Guarantee:	2 years