

Code: C72A-36

## PAL CAMERA **C72A-36** 720 TVL 3.6 mm

The C72A-36 camera is equipped with very high resolution Sony sensor. Due to above, this camera is perfect solution for surveillance systems requiring persons or vehicles recognition, for example at places like: buildings entrance, lobbies, lounges, etc. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance). OSD menu controller is placed on the cable. It allows to easily set or change the parameters and functions of the camera without move or unmount it.



Standard:	PAL
Sensor:	1/3 " Sony Super HAD II CCD
Digital Image Processor:	DSP Sony Effio-A
Resolution:	720 TVL
Lens:	3.6 mm
View angle:	67 ° (manufacturer data) 74 ° (our tests result)
Range of IR illumination:	20 m
S/N ratio:	52 dB
Video output:	1 Vpp / 75 Ω
Power supply:	12 V / 330 mA

Main features:	<ul style="list-style-type: none"><li>• Sense-UP - (Slow Shutter) - Increase the sensor sensitivity</li><li>• DIS - Digital Image Stabilization</li><li>• ATR - Wide Dynamic Range</li><li>• DNR - Digital Noise Reduction</li><li>• IR illuminator optimization</li><li>• EZOOM - Digital Zoom off</li><li>• HLC - High Light Compensation (spot)</li><li>• BLC - configurable Back Light Compensation</li><li>• Privacy zones - max. 15</li><li>• Motion Detection</li><li>• Sharpness - sharper image outlines</li><li>• Monitor type correction - LCD/CRT</li><li>• Day/Night mode - configurable</li></ul>
OSD menu:	✓
Housing:	Compact, Metal
Color:	Dark graphite
"Index of Protection":	IP66
Operation temp:	-20 °C ... 50 °C
Weight:	0.285 kg
Dimensions:	188 x 74 x 65 mm
Guarantee:	2 years