

Code: VD65-2812/2

PAL VANDALPROOF CAMERA **VD65-2812/2** 650 TVL 2.8 ... 12 mm

Vandal-proof camera in metal housing with high resolution Sony Super HAD II sensor and wide range of view angle adjustment. It is equipped with IR illuminator, which is turned on by twilight sensor when illumination conditions are low. Camera Dome cover is protected by metal cable against falling during installation works. It is equipped with OSD menu controller, which allows to set and change the camera parameters without the need to remove or move the camera.



Standard:	PAL
Sensor:	1/3 " Sony Super HAD II CCD
Resolution:	650 TVL
Lens:	2.8 ... 12 mm (adjusted by a screw driver, inside the housing)
View angle:	81 ° ... 23 ° (manufacturer data) 85 ° ... 29 ° (our tests result)
Range of IR illumination:	20 m
S/N ratio:	> 52 dB
Video output:	1 Vpp / 75 Ω
Power supply:	12 V / 300 mA
Main features:	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2-DNR - Digital Noise Reduction • HLC - High Light Compensation (spot) • BLC - configurable Back Light Compensation • AGC Motion Detection - max. 4 configurable zones • Privacy zones - max. 8 • Day/night mode - manual/auto • Monitor type correction - LCD/CRT • Sharpness - sharper image outlines
Vandal-proof:	✓
Permissible relative humidity:	max. 95 %
"Index of Protection":	IP66
Housing:	Dome - Metal



DATA SHEET

Color:	White
Operation temp:	-10 °C ... 50 °C
Weight:	0.74 kg
Dimensions:	Ø 140 x 93 mm
Supported languages:	English, Chinese, French, Spanish, Japanese, German, Portuguese, Russian
Guarantee:	2 years