

DATA SHEET

Code: VMT-271

MONITOR VGA, 3XVIDEO, HDMI, AUDIO, REMOTE CONTROLLER VMT-271 27 " VILUX

CCTV monitor in plastic housing. The LED matrix illumination technology allows to real colors reproduction, 40% lower current consumption and much lower failure rate compared to normal LCD monitors with CCFL illumination.

Monitor is perfect solution to work with PC, where there is a need to view the image from DVR in the same time. This model is equipped with all kinds of inputs, what allows to display an image from any kind of signals using in CCTV systems.

Interesting solution is placing the speakers of the back side of housing. It does not bother listening to the AUDIO from the recorder at the same time does not reduce the area of the monitor front panel.

The device is designed to continuous work in closed spaces.



Screen size:	27 "
Native resolution:	1920 x 1080 px
Aspect ratios:	16:9
Matrix type:	TFT-LCD color matrix
Matrix backlight:	In LED technology
Supported standards:	PAL/NTSC
Contrast:	1000 : 1
Brightness:	400 cd/m ²
View angle:	170 ° horizontal 170 ° vertical
Response time:	5 ms
Speakers built-in:	2 x 5 W
Signal connectors:	Composite Video (BNC) sockets: 2x in, 2x out 1x VGA 1x HDMI S-VIDEO Audio: 1x Jack (for VGA) 2x Cinch L/R (for Video 1/2)





DATA SHEET

Housing type:	Plastic
Monitor mounting standard:	VESA 100
Power supply:	24 V DC / 3 A (power adapter included)
Power consumption:	• < 40 W (operation) • < 1 W (Standby mode)
Monitor control:	OSD - by IR remote controller or monitor control keys
Main features:	 3D Comb Filter 3D Noise Reduction PIP and POP functions - picture in picture and two pictures side by side Auto Picture Adjustment
Operation temp:	-10 °C 50 °C
Weight:	6.07 kg
Dimensions:	• 655 x 470 x 188 mm (with stand) • 655 x 410 x 50 mm (without stand)
Supported languages:	English, Chinese, French, Spanish, German, Polish, Portuguese, Russian, Italian
Manufacturer / Brand:	VILUX
Guarantee:	2 years