

Code: MS-35AHD

MONITOR AHD, PAL **MS-35AHD** 4.3 "

Service color monitor is very helpful for CCTV system configuration. Due to small sizes it can be very quickly and easily connected to the camera or DVR for configuration their parameters.

The device is powered from battery or power supply adaptor. So, it is the perfect test tool for CCTV systems, as well as for other devices with AHD / PAL output. An additional advantage is the possibility to power the connected devices with DC 5/12V and max. 300mA current consumption, and also the long operation time. Monitor is equipped with plastic housing.



Standard:	AHD-H, AHD-M, AHD-L, PAL, NTSC
Screen size:	4.3 "
Native resolution:	480 x 272 px
Contrast:	400 : 1
Brightness:	250 cd/m ²
Response time:	8 ms
Image adjustment:	Configurable: brightness, contrast, saturation
Video input:	1 pcs - BNC cable included in the kit
Audio input:	1 pcs Jack socket
Sleep function:	—
Main features:	<ul style="list-style-type: none"> • UTP cables or phone lines connecting test with RJ-45 connectors, • DC 5V / 12V, max. 300mA power source, • Flashlight built-in, • RESET button
Battery power supply:	Li-Ion battery 3.7 V, 2600 mAh (included)
Power supply:	5 V DC (power adapter included)



DATA SHEET

Operation temp:	-30 °C ... 70 °C
Weight:	0.205 kg
Dimensions:	122 x 82 x 39 mm
Guarantee:	2 years
Supported languages:	English, Chinese, French, Spanish, German, Portuguese, Russian, Italian